
ISO-Venti Xtrem

28-870

09.04.2024

Article No.:

Print date:



Precautionary state	ments	
P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P280	Wear protective gloves and eye/face protection.	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations	
Hazard components for labelling		

2-Methylisothiazol-3(2H)-one

Supplemental hazard information EUH211

- Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- 2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. **Mixtures**



ΕN



cle No.: it date: sion:	28-870 09.04.2024 1.3	ISO-Venti Xtrem Revision date: 08.01.2024 Issue date: 08.01.2024	EN Page 2 / 9	
Descrip	tion Wate	r-thinnable lacquer on special acrylate dis	spersion base	
Classifi	cation according to	Regulation (EC) No 1272/2008 [CLP]		
EC No. CAS No Index No	. Desig	CH No. Ination ification: // Remark		weight-%
236-675 13463-6 022-006	7-7 titaniu -00-2 aerod	19489379-17 Im dioxide [in powder form containing ynamic diameter ≤ 10 µm] 2 H351	1 % or more of particles with	20 - 25
201-074 77-99-6	Propy	19486799-10 Iidynetrimethanol 2 H361fd		0,1 - 0,15
220-239 2682-20 613-326	-6 01-21 -4 2-Met -00-9 Acute 1B H3 (M = Speci Tox. 4 / Skir	20764690-50 hylisothiazol-3(2H)-one Tox. 3 H301 / Acute Tox. 3 H311 / A 314 / Eye Dam. 1 H318 / Skin Sens. 1A 10) / Aquatic Chronic 1 H410 (M = 1) / fic concentration limit (SCL): Skin Sens. H332 >= 3 / Skin Irrit. 2 H315 >= Corr. 1B H314 >= 10 / Acute Tox. 3 >= 25 / Aquatic Acute 1 H400 >= 3	A H317 / Aquatic Acute 1 H400 EUH071 1A H317 >= 0,0015 / Acute 5 / Eye Irrit. 2 H319 >= 5 B H331 >= 25 / Acute Tox. 4	< 0,025

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed** First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters



Article No.:	28-870	ISO-Venti Xtrem		
Print date:	09.04.2024	Revision date: 08.01.2024	EN	
Version:	1.3	Issue date: 08.01.2024	Page 3 / 9	

Provide a conveniently located respiratory protective device.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

No special measures are required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 8 °C and 30 °C. Protect from heat and direct sunlight.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] Index No. 022-006-00-2 / EC No. 236-675-5 / CAS No. 13463-67-7

WEL, TWA: 10 mg/m3 Remark: (inhalable fraction) WEL, TWA: 4 mg/m3 Remark: (respirable fraction)

Additional information

TWA : Long-term occupational exposure limit value STEL : short-term occupational exposure limit value Ceiling : peak limitation

DNEL:

2-Methylisothiazol-3(2H)-one Index No. 613-326-00-9 / EC No. 220-239-6 / CAS No. 2682-20-4 DNEL acute inhalative (local), Workers: 0,043 mg/m³



Article Print da Versior	ate:	28-870 09.04.2024 1.3	ISO-Venti Xtrem Revision date: 08.01.2024 Issue date: 08.01.2024	EN Page 4 / 9
	DNEL long DNEL acu DNEL long	g-term oral (repeate ite inhalative (local), g-term inhalative (lo	cal), Workers: 0,021 mg/m ³ d), Consumer: 0,027 mg/kg Consumer: 0,043 mg/m ³ cal), Consumer: 0,021 mg/m ³ Consumer: 0,053 mg/kg	
	Index No. 0 DNEL long	22-006-00-2 / EC N g-term inhalative (lo	n containing 1 % or more of pa o. 236-675-5 / CAS No. 13463 cal), Workers: 10 mg/m ³ d), Consumer: 700 mg/kg	rticles with aerodynamic diameter ≤ 10 μm] -67-7
	EC No. 201 DNEL lon DNEL lon DNEL lon DNEL lon	g-term inhalative (sy g-term oral (repeate g-term dermal (syste	7-99-6 emic), Workers: 0,94 mg/kg /stemic), Workers: 3,3 mg/m ³ d), Consumer: 0,34 mg/kg emic), Consumer: 0,34 mg/kg /stemic), Consumer: 0,58 mg/r	ŋ³
	PNEC:			
	Index No. 6 PNEC aqu PNEC aqu PNEC aqu PNEC aqu PNEC, so	thiazol-3(2H)-one 13-326-00-9 / EC N uatic, freshwater: 0,(uatic, marine water: uatic, intermittent rel il: 0,0471 mg/kg wage treatment plan	0,0033 mg/L lease: 0,0033 mg/L	20-4
	Index No. 0 PNEC aqu PNEC aqu PNEC aqu PNEC sec PNEC sec PNEC, so		o. 236-675-5 / CAS No. 13463 184 mg/L 0,0184 mg/L lease: 0,193 mg/L 1000 mg/kg r: 100 mg/kg	rticles with aerodynamic diameter ≤ 10 μm] -67-7
		od ventilation. This o		oom suction. If this should not be sufficient to keep aerosol and a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the weartime limits as specified by the manufacturer. Recommended respiratory protection articles: Inadequately ventilated workplaces and spraying procedures are necessary. Fresh air mask or short-time work combination filter A2-P2 are recommended.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

No special measures are necessary.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties



		00.070			
Article Print of		28-870 09.04.2024	ISO-Venti Xtrei Revision date:		EN
Versio		1.3	Issue date: 08.		Page 5/9
9.1.	Informatio	on on basic physi	cal and chemical	properties	
	Physical s	state:		Liquid	
	Colour:			white	
	Odour:			characteristic	
	Odour thr			No data available	
		pint/freezing poin		No data available	
	Initial boil	ing point and boi	ling range:	82 °C	
	F 1	114		Source: propan-2-ol	
	Flammabi	-		No data available	
		d upper explosior xplosion limit:	i limit:	0.8 Vol-%	
	Lower c			Method: literature value	
	Upper ex	plosion limit:		No data available	
	Flash point: Auto-ignition temperature:			No data available	
				No data available	
	Decompo	sition temperatur	e:	No data available	
	pH at 20 °	C:		4 - 5 / 100,0 weight-%	
	Viscosity	at °C:		45+/-3 dPas	
	Solubility(
		lubility at 20 °C:		partially soluble	
	Partition of	coefficient: n-octa	nol/water:	see section 12	
	Vapour pr	essure at 20 °C:		No data available	
		nd/or relative den	sity:		
	Density a	t 20 °C:		1,26 g/cm³ Method: DIN 53217	
	Relative v	apour density:		No data available	
		naracteristics:		not applicable	
9.2.	Other info			· · · · · · · · · · · · · · · · · · ·	
	Solid cont			52 weight-%	
	solvent co				
		solvents:		1 weight-%	
	Water:			47 weight-%	
000		Stability and roa	- 4114		

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.



Article No.:	28-870	ISO-Venti Xtrem
Print date:	09.04.2024	Revision date: 08.01.2024
Version:	1.3	Issue date: 08.01.2024

EN Page 6 / 9

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

2-Methylisothiazol-3(2H)-one oral, LD50, Rat 232 - 249 mg/kg dermal, LD50, Rabbit: 200 mg/kg inhalative (dust and mist), LC50, Rat: 0,11 mg/L (4 h) Method: OECD 403

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] oral, LD50, Rat: > 5000 mg/kg Method: OECD 425 dermal, LD50, Rabbit: > 2000 mg/kg inhalative (dust and mist), LC50, Rat 3,43 - 5,09 mg/L (4 h) Method: OECD 403

Propylidynetrimethanol oral, LD50, Rat: >= 14700 mg/kg dermal, LD50, Rat: > 500 mg/kg dermal, LD50, Rabbit: > 10000 mg/kg inhalative (dust and mist), LC50, Rat: > 0,29 mg/L (4 h)

Skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP] There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

12.1. Toxicity

2-Methylisothiazol-3(2H)-one Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 6 mg/L (96 h) Daphnia toxicity, EC50, Daphnia pulex (water flea): 1,6 mg/L (48 h) Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 0,157 mg/L (72 h) Bacteria toxicity, EC50, Activated sludge: 34,6 mg/L (3 h)

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]



Article Print d Versio	ate:	28-870 09.04.2024 1.3	ISO-Venti Xtrem Revision date: 08.01.2024 Issue date: 08.01.2024	EN Page 7 / 9
	Daphnia	a toxicity, LC50, Da	ynchus mykiss (Rainbow trout): > 100 mg/ ohnia magna: > 100 mg/L (48 h) dokirchneriella subcapitata: 16 mg/L (72 ł	
	Propylidy Fish tox Daphnia Algae to	netrimethanol kicity, LC50, Brachy a toxicity, EC50, Da	danio rerio (zebra-fish): > 100 mg/L (96 h phnia magna (Big water flea): 13000 mg/L nastrum capricornutum: > 1000 mg/L (72) . (48 h)
	Long-ter	m Ecotoxicity		
	Fish tox Method Daphnia	: OECD 210	e hales promelas (fathead minnow): 2,1 mg/ aphnia magna (Big water flea): 0,044 mg/L	
		netrimethanol a toxicity, NOEC, Da	aphnia magna (Big water flea): > 1000 mg/	/L (21 d)
12.2.	Persiste	nce and degradab	lity	
	Biodegr Method	sothiazol-3(2H)-one adation: 50 % (29 : OECD 301B dily biodegradable (
	Biodegr Method	metrimethanol adation: 100 % (2 : OECD 302B biodegradable (acc	8 d) cording to OECD criteria)	
12.3.	Bioaccu	mulative potential		
	Partition	sothiazol-3(2H)-one coefficient: n-octa : OECD 117		
		netrimethanol	ol /water (log P O/W):: -0,47	
	Bioconc	entration factor (B	CF)	
	•	sothiazol-3(2H)-one centration factor (BC		
			orm containing 1 % or more of particles wit CF), Oncorhynchus mykiss (Rainbow trout)	
		netrimethanol centration factor (BC	CF), Cyprinus carpio (Common Carp): < 17	,
12.4.	Mobility Toxicolog	in soil gical data are not av	ailable.	
12.5.		of PBT and vPvB a		
			re do not meet the PBT/vPvB criteria acco	rding to REACH, annex XIII.
12.6.		ne disrupting prop nation available.	erties	
12.7.		verse effects		
		Disposal consid	erations	
13.1.		eatment methods		
	Recomm Do not a	according to directi	Irface water or drains. This material and i	ts container must be disposed of in a safe way.Was erous waste. Dispose of waste according to applicab

legislation.

List of proposed waste codes/waste designations in accordance with EWC

2682-20-4



Article Print da /ersior	ate:	28-870 09.04.2024 1.3	ISO-Venti Xtrem Revision date: 08.01.2024 Issue date: 08.01.2024	EN Page 8 / 9
	Appropriat Recomme	s waste according to te disposal / Packa ndation	aint and varnish containing organic solvents Directive 2008/98/EC (waste framework dire ge ay be recycled. Vessels not properly emptied	ective).
		ransport informa		
			of this transport regulation.	
4.1.	UN numbe	r or ID number		
4.0		obinning nome	No data available	
4.Z.	UN proper	shipping name		
4.3.	Transport	hazard class(es)		
			No data available	
4.4.	Packing gr	roup	No data available	
15	Environmo	ental hazards	No data available	
		port (ADR/RID)	No data available	
	Marine poll		No data available	
	-	ecautions for user		
	case of an Advices on	accident or leakage. safe handling: see p		sons transporting the product know what to do i
	Further inf	ormation		
	Land trans	port (ADR/RID)		
	Tunnel rest	riction code	-	
	Sea transp	ort (IMDG)		
	EmS-No.		No data available	
4.7.	Maritime tr	ransport in bulk ac	cording to IMO instruments	
	No transpo	rt as bulk according	IBC - Code.	
ECT	TION 15: R	egulatory inform	ation	
5.1.	Safety, hea	alth and environme	ntal regulations/legislation specific for the	e substance or mixture
	EU legislat			
			ontrol of major-accident hazards involving cording to Directive 2012/18/EU.	g dangerous substances [Seveso-III-Directiv
	VOC produ	ct category: (Cat. A/	mitation of emissions of volatile organic (d) ; VOC limit value: 130 g/l roduct in a ready to use condition (in g/L): 13	•
	National re		,	
	Restrictior	s of occupation	ns under the Maternity Protection Directive (9	2/85/EEC) for expectant or nursing mothers.
			nent for juveniles according to the 'juvenile w	
		Safety Assessment lowing substances	of this mixture a chemical safety assessr	nent has been carried out:
	EC No.	Designa	-	REACH No.
	CAS No.	titanium	dioxide [in powder form containing 1 % or n	nore of particles 01-2119489379-17
	236-675-5		dynamic diameter < 10 uml	•
-	236-675-5 13463-67-7 201-074-9	with aero	odynamic diameter ≤ 10 μm] /netrimethanol	01-2119486799-10



Article No.:	28-870	ISO-Venti Xtrem	
Print date: Version:	09.04.2024	Revision date: 08.01.2024 Issue date: 08.01.2024	EN Page 9 / 9
version.	1.5	1550e uale. 00.01.2024	Fage 97 9

SECTION 16: Other information

Full text of classif	ication in	section 3:	
Carc. 2 / H351		Carcinogenicity	Suspected of causing cancer if inhaled.
Repr. 2 / H361fd		Reproductive toxicity	Suspected of damaging fertility. Suspected of
			damaging the unborn child.
Acute Tox. 3 / H30	1	Acute toxicity (oral)	Toxic if swallowed.
Acute Tox. 3 / H31	1		Toxic in contact with skin.
Acute Tox. 2 / H330	C	Acute toxicity (inhalative)	Fatal if inhaled.
Skin Corr. 1B / H31		Skin corrosion/irritation	Causes severe skin burns and eye damage.
Eye Dam. 1 / H318		Serious eye damage/eye irritation	Causes serious eye damage.
Skin Sens. 1A / H3		Respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Acute 1 / H		Hazardous to the aquatic environment	Very toxic to aquatic organisms.
Aquatic Chronic 1 /	H410	Hazardous to the aquatic environment	Very toxic to aquatic life with long lasting effects.
Classification pro	cedure		
		d used evaluation method according to regul	lation (EC) No 1272/2008 [CLP]
Skin Sens, 1		Respiratory or skin sensitisation	Calculation method.
Abbreviations and	1 acronyn		
ADR	•	ean Agreement concerning the International	Carriage of Dangerous Goods by Road
OEL		pational Exposure Limit Value	Carriage of Dangerous Cools by Road
BLV		ical Limit Value	
CAS	•	ical Abstracts Service	
CLP		fication, Labelling and Packaging	
CMR		nogenic, Mutagenic and Reprotoxic	
DIN		an Institute for Standardization / German indu	istrial standard
DNEL		ed No-Effect Level	
EAKV		ean Waste Catalogue Directive	
EC		ive Concentration	
EC		ean Community	
EN	•	ean Standard	
IATA-DGR		ational Air Transport Association – Dangerou	is Goods Regulations
IBC Code			nent of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI			I Instructions for the Safe Transport of Dangerous
-		s by Air	
IMDG Code		ational Maritime Code for Dangerous Goods	
ISO		ational Organization for Standardization	
LC		Concentration	
LD	Lethal	Dose	

MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
	•

- OECD Organisation for Economic Cooperation and Development
- PBT persistent, bioaccumulative, toxic
- PNEC Predicted No Effect Concentration
- REACH Registration, Evaluation, Authorisation and Restriction of Chemicals RID Regulations concerning the International Carriage of Dangerous Goods by Rail
- RID
 Regulations concerning the International Carriage of Danger

 UN
 United Nations
- VOCVolatile Organic CompoundsvPvBvery persistent and very bioaccumulative
- vi vo very persiste

Data sources

Data arise from reference works and literature.

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.