

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830

**JANSEN** 

Article No.: 37-770  
Print date 19.03.2021  
Version 1.14

Protect-Gel  
Revision date 16.01.2021  
Issue date 16.01.2021

EN  
Page 1 / 10

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Article No. (manufacturer/supplier): 37-770  
Trade name/designation: Protect-Gel  
nussbaum  
seidenglänzend

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses:**

Varnish / paint

**Uses advised against:**

Aware of any other information

**1.3. Details of the supplier of the safety data sheet**

**Supplier (manufacturer/importer/only representative/downstream user/distributor)**

P.A. Jansen GmbH u. Co., KG  
Hochstadenstraße 22  
D-53474 Bad Neuenahr-Ahrweiler  
Telephone: +49 2641 3897-0  
Telefax: +49 2641 3897-28  
Homepage: www.jansen.de

**Department responsible for information:**

laboratory  
E-mail (competent person) sicherheitsdatenblatt@jansen.de

**1.4. Emergency telephone number**

Emergency telephone number +49 2641 3897-51  
Only available during office hours.

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226 Flammable liquids Flammable liquid and vapour.

**2.2. Label elements**

The product is classified and labelled according to EC directives or corresponding national laws.

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



**Warning**

**Hazard statements**

H226 Flammable liquid and vapour.

**Precautionary statements**

P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.  
P501 Dispose of contents/container to industrial incineration plant.

**Hazard components for labelling**

No data available

**Supplemental hazard information**

EUH066 Repeated exposure may cause skin dryness or cracking.  
EUH208 Contains phthalic anhydride. May produce an allergic reaction.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition / information on ingredients**

Article No.: 37-770 Protect-Gel  
Print date 19.03.2021 Revision date 16.01.2021  
Version 1.14 Issue date 16.01.2021

EN  
Page 2 / 10

### 3.2. Mixtures

**Description** alkyd resin varnish

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

| EC No.<br>CAS No.<br>Index No.       | REACH No.<br>Designation<br>classification: // Remark   | weight-%   |
|--------------------------------------|---|------------|
| 918-481-9                            | 01-2119457273-39<br>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics<br>Asp. Tox. 1 H304  | 25 - 35    |
| 919-857-5                            | 01-2119463258-33<br>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics<br>Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / STOT SE 3 H336              | 15 - 20    |
| 245-018-1<br>22464-99-9              | 01-2119979088-21<br>2-ethylhexanoic acid, zirconium salt<br>Repr. 2 H361d   | 0,5 - 1    |
| 201-607-5<br>85-44-9<br>607-009-00-4 | 01-2119457017-41<br>phthalic anhydride<br>Acute Tox. 4 H302 / STOT SE 3 H335 / Skin Irrit. 2 H315 / Eye Dam. 1<br>H318 / Resp. Sens. 1 H334 / Skin Sens. 1 H317 | 0,2 - 0,25 |

#### Additional information

Full text of classification: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

#### Unsuitable extinguishing media

strong water jet

### 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

### 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

Article No.: 37-770  
Print date 19.03.2021  
Version 1.14

Protect-Gel  
Revision date 16.01.2021  
Issue date 16.01.2021

EN  
Page 3 / 10

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

### 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

### 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

#### Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

#### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limit values

Silicon dioxide

EC No. 231-545-4 / CAS No. 7631-86-9

WEL, TWA: 6 mg/m<sup>3</sup>

Remark: (Silica, amorphous; inhalable fraction)

WEL, TWA: 2,4 mg/m<sup>3</sup>

Remark: (Silica, amorphous; respirable fraction)

phthalic anhydride

Index No. 607-009-00-4 / EC No. 201-607-5 / CAS No. 85-44-9

WEL, TWA: 4 mg/m<sup>3</sup>

WEL, STEL: 12 mg/m<sup>3</sup>

Article No.: 37-770 Protect-Gel  
Print date 19.03.2021 Revision date 16.01.2021  
Version 1.14 Issue date 16.01.2021

EN  
Page 4 / 10

#### **Additional information**

TWA : Long-term occupational exposure limit value  
STEL : short-term occupational exposure limit value  
Ceiling : peak limitation

#### **DNEL:**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics  
EC No. 918-481-9

DNEL long-term dermal (systemic), Workers: 300 mg/kg  
DNEL long-term oral (repeated), Consumer: 300 mg/kg  
DNEL long-term dermal (systemic), Consumer: 300 mg/kg  
DNEL long-term inhalative (systemic), Consumer: 900 mg/m<sup>3</sup>

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics  
EC No. 919-857-5

DNEL long-term dermal (systemic), Workers: 208 mg/kg  
DNEL long-term inhalative (systemic), Workers: 871 mg/m<sup>3</sup>  
DNEL long-term oral (repeated), Consumer: 125 mg/kg  
DNEL long-term dermal (systemic), Consumer: 125 mg/kg  
DNEL long-term inhalative (systemic), Consumer: 185 mg/m<sup>3</sup>

Silicon dioxide

EC No. 231-545-4 / CAS No. 7631-86-9

DNEL acute inhalative (local), Workers: 4 mg/m<sup>3</sup>  
DNEL long-term inhalative (systemic), Workers: 4 mg/m<sup>3</sup>

#### **8.2. Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

#### **Personal protection equipment**

##### **Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear-time limits as specified by the manufacturer. Recommended respiratory protection articles : Inadequately ventilated workplaces and spraying procedures are necessary. Fresh air mask or short-time work combination filter A2-P2 are recommended.

##### **Hand protection**

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

##### **Eye/face protection**

Wear closely fitting protective glasses in case of splashes.

##### **Body protection**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

##### **Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

##### **Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

## **SECTION 9: Physical and chemical properties**

### **9.1. Information on basic physical and chemical properties**

#### **Appearance:**

**Physical state:** Liquid

**Appearance:** Liquid

**Colour:** brown

**Odour:** characteristic

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 37-770  
Print date 19.03.2021  
Version 1.14

Protect-Gel  
Revision date 16.01.2021  
Issue date 16.01.2021

EN  
Page 5 / 10

|  |  |
|--|--|
| <b>Odour threshold:</b>                              | <b>No data available</b>   |
| <b>pH at 20 °C:</b>                                  | <b>No data available</b>   |
| <b>Melting point/freezing point:</b>                 | <b>&lt; -20 °C</b><br>Source: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics                            |
| <b>Initial boiling point and boiling range:</b>      | <b>119 °C</b><br>Source: 1-methoxy-2-propanol  |
| <b>Flash point:</b>                                  | <b>41 °C</b><br>Method: EN ISO 1523  |
| <b>Evaporation rate:</b>                             | <b>No data available</b>   |
| <b>flammability</b>                                  |  |
| <b>Burning time:</b>                                 | <b>No data available</b>   |
| <b>Upper/lower flammability or explosive limits:</b> |  |
| <b>Lower explosion limit:</b>                        | <b>0,6 Vol-%</b><br>Method: literature value<br>Source: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics |
| <b>Upper explosion limit:</b>                        | <b>7 Vol-%</b><br>Method: literature value<br>Source: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics   |
| <b>Vapour pressure at 20 °C:</b>                     | <b>not checked</b>   |
| <b>Vapour density:</b>                               | <b>No data available</b>   |
| <b>Relative density:</b>                             |  |
| <b>Density at 20 °C:</b>                             | <b>0,93 g/cm<sup>3</sup></b><br>Method: DIN 53217  |
| <b>Solubility(ies):</b>                              |  |
| <b>Water solubility at 20 °C:</b>                    | <b>insoluble</b>   |
| <b>Partition coefficient: n-octanol/water:</b>       | <b>see section 12</b>  |
| <b>Auto-ignition temperature:</b>                    | <b>231 °C</b><br>Source: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics                                |
| <b>Decomposition temperature:</b>                    | <b>No data available</b>   |
| <b>Viscosity at °C:</b>                              | <b>thixotropic</b>   |
| <b>Kinematic viscosity at 20 °C::</b>                | <b>&gt; 20,5 mm<sup>2</sup>/s</b>  |
| <b>Explosive properties:</b>                         | <b>No data available</b>   |
| <b>Oxidising properties:</b>                         | <b>No data available</b>   |
| 9.2. <b>Other information</b>                        |  |
| <b>Solid content:</b>                                | <b>57 weight-%</b>   |
| <b>solvent content:</b>                              |  |
| <b>Organic solvents:</b>                             | <b>43 weight-%</b>   |
| <b>Water:</b>  | <b>0 weight-%</b>  |
| <b>Solvent separation test:</b>                      | <b>&lt; 3 weight-% (ADR/RID)</b>   |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

### 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 37-770  
Print date 19.03.2021  
Version 1.14

Protect-Gel  
Revision date 16.01.2021  
Issue date 16.01.2021

EN  
Page 6 / 10

**10.4. Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

**10.5. Incompatible materials**

not applicable

**10.6. Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

**SECTION 11: Toxicological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

No data on preparation itself available.

**11.1. Information on toxicological effects**

**Acute toxicity**

Linseed oil

oral, LD50, Rat: > 5000 mg/kg

phthalic anhydride

oral, LD50, Rat: > 1530 mg/kg

2-ethylhexanoic acid, zirconium salt

oral, LD50, Rat: > 5000 mg/kg

dermal, LD50, Rabbit: > 5000 mg/kg

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 5000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: > 4951 mg/L (4 h)

Method: OECD 403

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 5000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: > 18,5 mg/L (4 h)

Silicon dioxide

oral, LD50, Rat: > 5000 mg/kg

dermal, LD50, Rabbit: > 5000 mg/kg

inhalative (dust and mist), LC50, Rat: > 0,477 mg/L (4 h)

**Skin corrosion/irritation; Serious eye damage/eye irritation**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Skin (4 h)

mild irritant.

eyes

mild irritant.

**Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Based on available data, the classification criteria are not met.

**STOT-single exposure; STOT-repeated exposure**

phthalic anhydride

Specific target organ toxicity (single exposure), Irritation

Irritation to respiratory tract

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Specific target organ toxicity (single exposure), drowsiness

Narcotic effects

**Aspiration hazard**

Article No.: 37-770 Protect-Gel  
Print date 19.03.2021 Revision date 16.01.2021  
Version 1.14 Issue date 16.01.2021

EN  
Page 7 / 10

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics  
Aspiration hazard

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics  
Aspiration hazard

#### **Practical experience/human evidence**

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

#### **Overall Assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

#### **Remark**

There is no information available on the preparation itself .

### **SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]  
There is no information available on the preparation itself .  
Do not allow to enter into surface water or drains.

#### **12.1. Toxicity**

Linseed oil

Fish toxicity, LC50, Danio rerio (zebrafish): > 1000 mg/L (96 h)

2-ethylhexanoic acid, zirconium salt

Fish toxicity, LC50, Oryzias latipes: > 100 mg/L (96 h)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): > 1000 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna: > 1000 mg/L (48 h)

Method: OECD 202

Algae toxicity, EC50, Pseudokirchneriella subcapitata: > 1000 mg/L

Method: OECD 201

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): > 1000 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna: > 1000 mg/L (48 h)

Method: OECD 202

Algae toxicity, EC50, Pseudokirchneriella subcapitata: > 1000 mg/L (72 h)

Method: OECD 201

Silicon dioxide

Fish toxicity, LC50, Danio rerio (zebrafish): > 10000 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna: > 10000 mg/L (24 h)

Method: OECD 202

#### **12.2. Persistence and degradability**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Biodegradation: 80 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301F

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Biodegradation: 80 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

#### **12.3. Bioaccumulative potential**

phthalic anhydride

Partition coefficient n-octanol /water (log P O/W):: 1,6

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Partition coefficient n-octanol /water (log P O/W):: 5 - 6,7



**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 37-770  
Print date 19.03.2021  
Version 1.14

Protect-Gel  
Revision date 16.01.2021  
Issue date 16.01.2021

EN  
Page 8 / 10

**Bioconcentration factor (BCF)**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics  
Bioconcentration factor (BCF): 10 - 2500

**12.4. Mobility in soil**

Toxicological data are not available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Appropriate disposal / Product Recommendation**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**List of proposed waste codes/waste designations in accordance with EWC**

080111\* Waste paint and varnish containing organic solvents or other dangerous substances

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

**Appropriate disposal / Package Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**14.1. UN number**

UN 1263

**14.2. UN proper shipping name**

Land transport (ADR/RID): Paint  
Sea transport (IMDG): PAINT  
Air transport (ICAO-TI / IATA-DGR): Paint

**14.3. Transport hazard class(es)**

Land transport (ADR/RID): Not goods of class 3  
in containers > 450 l Class 3  
Sea transport (IMDG) 3  
for packages < = 450 litres Transport in accordance with 2.3.2.5 of the IMDG Code.  
Air transport (ICAO-TI / IATA-DGR) 3

**14.4. Packing group**

III

**14.5. Environmental hazards**

Land transport (ADR/RID) No data available  
Marine pollutant No data available

**14.6. Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Further information**

**Land transport (ADR/RID)**

tunnel restriction code D/E

**Sea transport (IMDG)**

EmS-No. F-E, S-E

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable



Article No.: 37-770  
Print date 19.03.2021  
Version 1.14

Protect-Gel  
Revision date 16.01.2021  
Issue date 16.01.2021

EN  
Page 9 / 10

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

**Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]**

Category: P5c FLAMMABLE LIQUIDS

Quantity 1: 5000 t / Quantity 2: 50000 t

**Directive 2004/42/EC on the limitation of emissions of volatile organic compounds**

VOC product category: (Cat. A/e) ; VOC limit value: 400 g/l

Maximum VOC content (g/L) of the product in a ready to use condition: 400

#### National regulations

#### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

### 15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

| EC No.<br>CAS No.       | Designation  | REACH No.        |
|-------------------------|--|------------------|
| 918-481-9               | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics | 01-2119457273-39 |
| 919-857-5               | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics  | 01-2119463258-33 |
| 245-018-1<br>22464-99-9 | 2-ethylhexanoic acid, zirconium salt                                   | 01-2119979088-21 |
| 201-607-5<br>85-44-9    | phthalic anhydride   | 01-2119457017-41 |

## SECTION 16: Other information

### Full text of classification in section 3:

|                      |                                   |  |
|----------------------|-----------------------------------|--|
| Asp. Tox. 1 / H304   | Aspiration hazard                 | May be fatal if swallowed and enters airways.                              |
| Flam. Liq. 3 / H226  | Flammable liquids                 | Flammable liquid and vapour.   |
| STOT SE 3 / H336     | STOT-single exposure              | May cause drowsiness or dizziness.   |
| Repr. 2 / H361d      | Reproductive toxicity             | Suspected of damaging the unborn child.                                    |
| Acute Tox. 4 / H302  | Acute toxicity (oral)             | Harmful if swallowed.  |
| STOT SE 3 / H335     | STOT-single exposure              | May cause respiratory irritation.  |
| Skin Irrit. 2 / H315 | Skin corrosion/irritation         | Causes skin irritation.  |
| Eye Dam. 1 / H318    | Serious eye damage/eye irritation | Causes serious eye damage.   |
| Resp. Sens. 1 / H334 | Respiratory or skin sensitisation | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| Skin Sens. 1 / H317  | Respiratory or skin sensitisation | May cause an allergic skin reaction.                                       |

### Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3 Flammable liquids On basis of test data.

### Abbreviations and acronyms

|          |   |
|----------|---|
| ADR      | European Agreement concerning the International Carriage of Dangerous Goods by Road                 |
| OEL      | Occupational Exposure Limit Value   |
| BLV      | Biological Limit Value  |
| CAS      | Chemical Abstracts Service  |
| CLP      | Classification, Labelling and Packaging   |
| CMR      | Carcinogenic, Mutagenic and Reprotoxic  |
| DIN      | German Institute for Standardization / German industrial standard                                   |
| DNEL     | Derived No-Effect Level   |
| EAKV     | European Waste Catalogue Directive  |
| EC       | Effective Concentration   |
| EC       | European Community  |
| EN       | European Standard   |
| IATA-DGR | International Air Transport Association – Dangerous Goods Regulations                               |
| IBC Code | International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk |

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 37-770  
Print date 19.03.2021  
Version 1.14

Protect-Gel  
Revision date 16.01.2021  
Issue date 16.01.2021

EN  
Page 10 / 10

---

|           |   |
|-----------|---|
| ICAO-TI   | International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air |
| IMDG Code | International Maritime Code for Dangerous Goods   |
| ISO       | International Organization for Standardization  |
| LC        | Lethal Concentration  |
| LD        | Lethal Dose   |
| MARPOL    | Maritime Pollution: The International Convention for the Prevention of Pollution from Ships                       |
| OECD      | Organisation for Economic Cooperation and Development   |
| PBT       | persistent, bioaccumulative, toxic  |
| PNEC      | Predicted No Effect Concentration   |
| REACH     | Registration, Evaluation, Authorisation and Restriction of Chemicals  |
| RID       | Regulations concerning the International Carriage of Dangerous Goods by Rail                                      |
| UN        | United Nations  |
| VOC       | Volatile Organic Compounds  |
| vPvB      | very persistent and very bioaccumulative  |

**Data sources:**

Data arise from reference works and literature.

**Further information**

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.