

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.:	16-20	Ultra-Primer	
Print date	09.04.2024	Revision date	04.01.2024
Version	1.87	Issue date	04.01.2024
		EN	
		Page 1 / 13	

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Article No. (manufacturer/supplier):	16-20
Trade name/designation	Ultra-Primer
	weiß
	seidenmatt
	UFI: TE1M-DJQA-VG0J-DJ15

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses:**

Primer

**Uses advised against:**

Aware of any other information

**1.3. Details of the supplier of the safety data sheet**

**Supplier (manufacturer/importer/only representative/downstream user/distributor)**

P.A. Jansen GmbH u. Co., KG	
Hochstadenstraße 22	Telephone: +49 2641 3897-0
D-53474 Bad Neuenahr-Ahrweiler	Telefax: +49 2641 3897-28
	Homepage: www.jansen.de

**Department responsible for information:**

laboratory

E-mail (competent person) sicherheitsdatenblatt@jansen.de

**1.4. Emergency telephone number**

Emergency telephone number	+49 2641 3897-51
Only available during office hours.	

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.

**2.2. Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



**Warning**

**Hazard statements**

H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P370 + P378.6	In case of fire: Use carbon dioxide, extinguishing powder or alcohol-resistant foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard components for labelling**

Hydrocarbons, C9, aromatics

**Supplemental hazard information**

EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 16-20 Ultra-Primer  
Print date 09.04.2024 Revision date 04.01.2024  
Version 1.87 Issue date 04.01.2024

EN  
Page 2 / 13

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Description** plastic ground

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

EC No. CAS No. Index No.	REACH No. Designation classification: // Remark	weight-%
236-675-5 13463-67-7 022-006-00-2	01-2119489379-17 titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] Carc. 2 H351	15 - 20
918-668-5	01-2119455851-35 Hydrocarbons, C9, aromatics Flam. Liq. 3 H226 / STOT SE 3 H335 / Aquatic Chronic 2 H411 / Asp. Tox. 1 H304 / STOT SE 3 H336 / EUH066	10 - 12,5
204-658-1 123-86-4 607-025-00-1	01-2119485493-29 n-butyl acetate Flam. Liq. 3 H226 / STOT SE 3 H336 / EUH066	10 - 12,5
919-857-5	01-2119463258-33 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / STOT SE 3 H336 / EUH066	5 - 7
203-539-1 107-98-2 603-064-00-3	01-2119457435-35 1-methoxy-2-propanol Flam. Liq. 3 H226 / STOT SE 3 H336	5 - 7

**Additional information**

Full text of classification: see section 16

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**Following ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

Suitable extinguishing media

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 16-20 Ultra-Primer  
Print date 09.04.2024 Revision date 04.01.2024  
Version 1.87 Issue date 04.01.2024

EN  
Page 3 / 13

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

**Unsuitable extinguishing media**

strong water jet

**5.2. Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

**5.3. Advice for firefighters**

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

**6.3. Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

**6.4. Reference to other sections**

Observe protective provisions (see section 7 and 8).

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advices on safe handling**

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

**Further information**

Vapours are heavier than air. Vapours form explosive mixtures with air.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

**Hints on joint storage**

Keep away from strongly acidic and alkaline materials as well as oxidizers.

**Further information on storage conditions**

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

**7.3. Specific end use(s)**

Observe technical data sheet. Observe instructions for use.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limit values**

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Index No. 022-006-00-2 / EC No. 236-675-5 / CAS No. 13463-67-7

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**



Article No.: 16-20 Ultra-Primer  
Print date 09.04.2024 Revision date 04.01.2024  
Version 1.87 Issue date 04.01.2024

EN  
Page 4 / 13

WEL, TWA: 10 mg/m<sup>3</sup>  
Remark: (inhalable fraction)  
WEL, TWA: 4 mg/m<sup>3</sup>  
Remark: (respirable fraction)

Barium sulfate  
EC No. 231-784-4 / CAS No. 7727-43-7

WEL, TWA: 10 mg/m<sup>3</sup>  
Remark: (inhalable fraction)  
WEL, TWA: 4 mg/m<sup>3</sup>  
Remark: (respirable fraction)

Kaolin  
EC No. 310-194-1 / CAS No. 1332-58-7

WEL, TWA: 2 mg/m<sup>3</sup>  
Remark: (respirable fraction)

1-methoxy-2-propanol  
Index No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

WEL, TWA: 375 mg/m<sup>3</sup>; 100 ppm  
WEL, STEL: 560 mg/m<sup>3</sup>; 150 ppm  
Remark: (may be absorbed through the skin)

**Additional information**

TWA : Long-term occupational exposure limit value  
STEL : short-term occupational exposure limit value  
Ceiling : peak limitation

**DNEL:**

1-methoxy-2-propanol  
Index No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

DNEL long-term dermal (systemic), Workers: 183 mg/kg  
DNEL acute inhalative (local), Workers: 553,5 mg/m<sup>3</sup>  
DNEL long-term inhalative (systemic), Workers: 369 mg/m<sup>3</sup>  
DNEL long-term oral (repeated), Consumer: 33 mg/kg  
DNEL long-term dermal (systemic), Consumer: 78 mg/kg  
DNEL long-term inhalative (systemic), Consumer: 43,9 mg/m<sup>3</sup>

n-butyl acetate  
Index No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

DNEL acute dermal, short-term (systemic), Workers: 11 mg/kg  
DNEL long-term dermal (systemic), Workers: 11 mg/kg  
DNEL acute inhalative (local), Workers: 600 mg/m<sup>3</sup>  
DNEL acute inhalative (systemic), Workers: 600 mg/m<sup>3</sup>  
DNEL long-term inhalative (local), Workers: 300 mg/m<sup>3</sup>  
DNEL long-term inhalative (systemic), Workers: 300 mg/m<sup>3</sup>  
DNEL short-term oral (acute), Consumer: 2 mg/kg  
DNEL long-term oral (repeated), Consumer: 2 mg/kg  
DNEL acute dermal, short-term (systemic), Consumer: 6 mg/kg  
DNEL long-term dermal (systemic), Consumer: 6 mg/kg  
DNEL acute inhalative (local), Consumer: 300 mg/m<sup>3</sup>  
DNEL acute inhalative (systemic), Consumer: 300 mg/m<sup>3</sup>  
DNEL long-term inhalative (local), Consumer: 35,7 mg/m<sup>3</sup>  
DNEL long-term inhalative (systemic), Consumer: 35,7 mg/m<sup>3</sup>

Hydrocarbons, C9, aromatics  
EC No. 918-668-5

DNEL long-term dermal (systemic), Workers: 25 mg/kg  
DNEL long-term inhalative (systemic), Workers: 150 mg/m<sup>3</sup>  
DNEL long-term oral (repeated), Consumer: 11 mg/kg  
DNEL long-term dermal (systemic), Consumer: 11 mg/kg  
DNEL long-term inhalative (systemic), Consumer: 32 mg/m<sup>3</sup>

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics  
EC No. 919-857-5

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**



Article No.: 16-20 Ultra-Primer  
Print date 09.04.2024 Revision date 04.01.2024  
Version 1.87 Issue date 04.01.2024

EN  
Page 5 / 13

DNEL long-term dermal (systemic), Workers: 300 mg/kg  
DNEL long-term inhalative (systemic), Workers: 1500 mg/m<sup>3</sup>  
DNEL long-term oral (repeated), Consumer: 300 mg/kg  
DNEL long-term dermal (systemic), Consumer: 300 mg/kg  
DNEL long-term inhalative (systemic), Consumer: 900 mg/m<sup>3</sup>

Barium sulfate

EC No. 231-784-4 / CAS No. 7727-43-7

DNEL long-term oral (repeated), Workers: 10 mg/kg  
DNEL long-term inhalative (local), Workers: 10 mg/m<sup>3</sup>  
DNEL long-term inhalative (systemic), Workers: 10 mg/m<sup>3</sup>  
DNEL long-term oral (repeated), Consumer: 13000 mg/kg  
DNEL long-term inhalative (systemic), Consumer: 10 mg/m<sup>3</sup>

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Index No. 022-006-00-2 / EC No. 236-675-5 / CAS No. 13463-67-7

DNEL long-term inhalative (local), Workers: 10 mg/m<sup>3</sup>  
DNEL long-term oral (repeated), Consumer: 700 mg/kg

**PNEC:**

1-methoxy-2-propanol

Index No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

PNEC aquatic, freshwater: 10 mg/L  
PNEC aquatic, marine water: 1 mg/L  
PNEC aquatic, intermittent release: 100 mg/L  
PNEC sediment, freshwater: 52,3 mg/kg  
PNEC sediment, marine water: 5,2 mg/kg  
PNEC, soil: 4,59 mg/kg  
PNEC sewage treatment plant (STP): 100 mg/L

n-butyl acetate

Index No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

PNEC aquatic, freshwater: 0,18 mg/L  
PNEC aquatic, marine water: 0,018 mg/L  
PNEC aquatic, intermittent release: 0,36 mg/L  
PNEC sediment, freshwater: 0,981 mg/kg  
PNEC sediment, marine water: 0,0981 mg/kg  
PNEC, soil: 0,093 mg/kg  
PNEC sewage treatment plant (STP): 35,6 mg/L

Barium sulfate

EC No. 231-784-4 / CAS No. 7727-43-7

PNEC aquatic, freshwater: 0,115 mg/L  
PNEC sediment, freshwater: 600,4 mg/kg  
PNEC, soil: 207,7 mg/kg  
PNEC sewage treatment plant (STP): 62,2 mg/L

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Index No. 022-006-00-2 / EC No. 236-675-5 / CAS No. 13463-67-7

PNEC aquatic, freshwater: 0,184 mg/L  
PNEC aquatic, marine water: 0,0184 mg/L  
PNEC aquatic, intermittent release: 0,193 mg/L  
PNEC sediment, freshwater: 1000 mg/kg  
PNEC sediment, marine water: 100 mg/kg  
PNEC, soil: 100 mg/kg  
PNEC sewage treatment plant (STP): 100 mg/L

**8.2. Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

**Personal protection equipment**

**Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear-time limits as specified by the manufacturer. Recommended respiratory protection articles: Inadequately ventilated workplaces and spraying procedures are necessary. Fresh air mask or short-time work combination filter A2-P2 are

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 16-20  
Print date 09.04.2024  
Version 1.87

Ultra-Primer  
Revision date 04.01.2024  
Issue date 04.01.2024

EN  
Page 6 / 13

recommended.

**Hand protection**

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Eye/face protection**

Wear closely fitting protective glasses in case of splashes.

**Body protection**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

**Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

**SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

<b>Physical state:</b>	<b>Liquid</b>
<b>Colour:</b>	<b>white</b>
<b>Odour:</b>	<b>characteristic</b>
<b>Odour threshold:</b>	<b>No data available</b>
<b>Melting point/freezing point:</b>	<b>-96 °C</b> Source: 1-methoxy-2-propanol
<b>Initial boiling point and boiling range:</b>	<b>80 °C</b> Source: Benzene
<b>Flammability:</b>	<b>Flammable liquid and vapour.</b>
<b>Lower and upper explosion limit:</b>	
<b>Lower explosion limit:</b>	<b>0,7 Vol-%</b> Method: literature value Source: Hydrocarbons, C9, aromatics
<b>Upper explosion limit:</b>	<b>7,5 Vol-%</b> Method: literature value Source: n-butyl acetate
<b>Flash point:</b>	<b>25 °C</b> Method: EN ISO 1523
<b>Auto-ignition temperature:</b>	<b>400 °C</b> Source: Hydrocarbons, C9, aromatics
<b>Decomposition temperature:</b>	<b>No data available</b>
<b>pH at 20 °C:</b>	<b>No data available</b>
<b>Cinematic viscosity (40°C):</b>	<b>&gt; 700 mm<sup>2</sup>/s</b>
<b>Viscosity at 23 °C:</b>	<b>60 s 6 mm</b> Method: DIN 53211
<b>Solubility(ies):</b>	
<b>Water solubility at 20 °C:</b>	<b>insoluble</b>
<b>Partition coefficient: n-octanol/water:</b>	<b>see section 12</b>
<b>Vapour pressure at 20 °C:</b>	<b>11,7 mbar</b> Source: 1-methoxy-2-propanol
<b>Density and/or relative density:</b>	
<b>Density at 20 °C:</b>	<b>1,44 g/cm<sup>3</sup></b>



**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 16-20  
Print date 09.04.2024  
Version 1.87

Ultra-Primer  
Revision date 04.01.2024  
Issue date 04.01.2024

EN  
Page 7 / 13

Method: DIN 53217

**Relative vapour density:**

**No data available**

**particle characteristics:**

**not applicable**

**9.2. Other information**

**Solid content:**

**67 weight-%**

**solvent content:**

**Organic solvents:**

**33 weight-%**

**Water:**

**0 weight-%**

**Solvent separation test:**

**< 3 weight-% (ADR/RID)**

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No information available.

**10.2. Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

**10.3. Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

**10.4. Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

**10.5. Incompatible materials**

not applicable

**10.6. Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

Kaolin

oral, LD50, Rat: > 5000 mg/kg

dermal, LD50, Rat: > 5000 mg/kg

1-methoxy-2-propanol

oral, LD50, Rat: 4016 mg/kg

dermal, LD50, Rabbit: > 2000 mg/kg

inhalative (vapours), LC50, Rat: 27,596 mg/L (6 h)

n-butyl acetate

oral, LD50, Rat: 10760 mg/kg

Method: OECD 423

dermal, LD50, Rabbit: 14112 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: > 21 mg/L (4 h)

Method: OECD 403

Hydrocarbons, C9, aromatics

oral, LD50, Rat: 2000 - 5000 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 2000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: > 10,2 mg/L (4 h)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 5000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: > 18,5 mg/L (4 h)

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**



Article No.: 16-20 Ultra-Primer  
Print date 09.04.2024 Revision date 04.01.2024  
Version 1.87 Issue date 04.01.2024

EN  
Page 8 / 13

Barium sulfate  
oral, LD50, Rat: > 5000 mg/kg  
Method: OECD 401

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]  
oral, LD50, Rat: > 5000 mg/kg  
Method: OECD 425  
dermal, LD50, Rabbit: > 2000 mg/kg  
inhalative (dust and mist), LC50, Rat 3,43 - 5,09 mg/L (4 h)  
Method: OECD 403

**Skin corrosion/irritation; Serious eye damage/eye irritation**

1-methoxy-2-propanol  
eyes, Rabbit  
mild irritant.

n-butyl acetate  
Skin (4 h)  
Method: OECD 404  
slightly irritant  
eyes, Rabbit  
Method: OECD 405  
slightly irritant

Hydrocarbons, C9, aromatics  
eyes, Rabbit (24 h)  
mild irritant.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics  
Skin (4 h)  
mild irritant.  
eyes  
mild irritant.

**Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Based on available data, the classification criteria are not met.

**STOT-single exposure; STOT-repeated exposure**

May cause drowsiness or dizziness.

1-methoxy-2-propanol  
Specific target organ toxicity (single exposure), drowsiness

n-butyl acetate  
Specific target organ toxicity (single exposure), drowsiness

Hydrocarbons, C9, aromatics  
Specific target organ toxicity (single exposure), Irritation  
Irritation to respiratory tract  
Specific target organ toxicity (single exposure), drowsiness  
Narcotic effects

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics  
Specific target organ toxicity (single exposure), drowsiness  
Narcotic effects

**Aspiration hazard**

Hydrocarbons, C9, aromatics  
Aspiration hazard

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics  
Aspiration hazard

**Practical experience/human evidence**

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the



Article No.: 16-20 Ultra-Primer  
Print date 09.04.2024 Revision date 04.01.2024  
Version 1.87 Issue date 04.01.2024

EN  
Page 9 / 13

aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

#### **Overall assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

#### **Remark**

There is no information available on the preparation itself .

#### **11.2. Information on other hazards**

##### **Endocrine disrupting properties**

No information available.

### **SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

#### **12.1. Toxicity**

##### **Kaolin**

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 100 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna: > 1100 mg/L (48 h)

Method: OECD 202

Algae toxicity, EC50, Scenedesmus subspicatus: > 100 mg/L (72 h)

Method: OECD 201

##### **1-methoxy-2-propanol**

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): > 100 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 100 mg/L (48 h)

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: > 1000 mg/L (72 h)

Bacteria toxicity, IC50, Activated sludge: 1000 mg/L (3 h)

Method: OECD 209

##### **n-butyl acetate**

Fish toxicity, LC50, Pimephales promelas: 18 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 44 mg/L (48 h)

Method: OECD 202

Algae toxicity, ErC50, Desmodesmus subspicatus: 397 mg/L (72 h)

Method: OECD 201

Cell proliferation inhibition test

Bacteria toxicity, EC50: 356 mg/L (40 h)

##### **Hydrocarbons, C9, aromatics**

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 9,2 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 3,2 mg/L (48 h)

Method: OECD 202

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 2,629 mg/L (72 h)

Method: OECD 201

##### **Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics**

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): > 1000 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna: > 1000 mg/L (48 h)

Method: OECD 202

Algae toxicity, EC50, Pseudokirchneriella subcapitata: > 1000 mg/L (72 h)

Method: OECD 201

##### **titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]**

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): > 100 mg/L (96 h)

Daphnia toxicity, LC50, Daphnia magna: > 100 mg/L (48 h)

Algae toxicity, EC50, Pseudokirchneriella subcapitata: 16 mg/L (72 h)

#### **Long-term Ecotoxicity**

Article No.: 16-20 Ultra-Primer  
Print date 09.04.2024 Revision date 04.01.2024  
Version 1.87 Issue date 04.01.2024

EN  
Page 10 / 13

Harmful to aquatic life with long lasting effects.

n-butyl acetate

Daphnia toxicity, NOEC, Daphnia magna: 23 mg/L (21 d)

Method: OECD 211

Algae toxicity, NOEC, Pseudokirchneriella subcapitata: 105 mg/L (72 h)

#### 12.2. Persistence and degradability

Kaolin

Biodegradation:

Not readily biodegradable (according to OECD criteria)

1-methoxy-2-propanol

Biodegradation: 96 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301E

n-butyl acetate

Biodegradation: 83 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301D/ EEC 92/69/V, C.4-E

Hydrocarbons, C9, aromatics

Biodegradation, Degree of elimination: 89 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301F

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Biodegradation: 80 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

#### 12.3. Bioaccumulative potential

1-methoxy-2-propanol

Partition coefficient n-octanol /water (log P O/W): 0,37

n-butyl acetate

Partition coefficient n-octanol /water (log P O/W): 2,3

Method: OECD 117

Hydrocarbons, C9, aromatics

Partition coefficient n-octanol /water (log P O/W): 3,7 - 4,5

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Partition coefficient n-octanol /water (log P O/W): 5 - 6,7

#### Bioconcentration factor (BCF)

1-methoxy-2-propanol

Bioconcentration factor (BCF): < 100

n-butyl acetate

Bioconcentration factor (BCF): 15,3

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Bioconcentration factor (BCF): 10 - 2500

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Bioconcentration factor (BCF), Oncorhynchus mykiss (Rainbow trout): 19 - 352

#### 12.4. Mobility in soil

n-butyl acetate

Surface tension: 61,3 mN/m

Method: OECD 115

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

No information available.

#### 12.7. Other adverse effects

No information available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**Appropriate disposal / Product  
Recommendation**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 16-20 Ultra-Primer  
Print date 09.04.2024 Revision date 04.01.2024  
Version 1.87 Issue date 04.01.2024

EN  
Page 11 / 13

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Dispose of waste according to applicable legislation.

**List of proposed waste codes/waste designations in accordance with EWC**

080111\* Waste paint and varnish containing organic solvents or other dangerous substances

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

**Appropriate disposal / Package**

**Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**14.1. UN number or ID number**

UN 1263

**14.2. UN proper shipping name**

Land transport (ADR/RID): Paint  
Sea transport (IMDG): PAINT  
Air transport (ICAO-TI / IATA-DGR): Paint

**14.3. Transport hazard class(es)**

Land transport (ADR/RID): Not goods of class 3  
in containers > 450 l Class 3  
Sea transport (IMDG) 3  
for packages ≤ 450 litres Transport in accordance with 2.3.2.5 of the IMDG Code.  
Air transport (ICAO-TI / IATA-DGR) 3

**14.4. Packing group**

III

**14.5. Environmental hazards**

Land transport (ADR/RID) No data available  
Marine pollutant No data available

**14.6. Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Further information**

**Land transport (ADR/RID)**

Tunnel restriction code D/E

**Sea transport (IMDG)**

EmS-No. F-E, S-E

**14.7. Maritime transport in bulk according to IMO instruments**

No transport as bulk according IBC - Code.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]**

Category: P5c FLAMMABLE LIQUIDS

Quantity 1: 5000 t / Quantity 2: 50000 t

**Directive 2004/42/EC on the limitation of emissions of volatile organic compounds**

VOC product category: (Cat. A/i) ; VOC limit value: 500 g/l

Maximum VOC content of the product in a ready to use condition (in g/L): 500

**National regulations**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 16-20 Ultra-Primer  
Print date 09.04.2024 Revision date 04.01.2024  
Version 1.87 Issue date 04.01.2024

EN  
Page 12 / 13

**15.2. Chemical Safety Assessment**

**For the following substances of this mixture a chemical safety assessment has been carried out:**

EC No. CAS No.	Designation	REACH No.
236-675-5 13463-67-7	titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]	01-2119489379-17
918-668-5	Hydrocarbons, C9, aromatics	01-2119455851-35
204-658-1 123-86-4	n-butyl acetate	01-2119485493-29
919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics	01-2119463258-33
203-539-1 107-98-2	1-methoxy-2-propanol	01-2119457435-35

**SECTION 16: Other information**

**Full text of classification in section 3:**

Carc. 2 / H351	Carcinogenicity	Suspected of causing cancer if inhaled.
Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.

**Classification procedure**

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3	Flammable liquids	On basis of test data.
STOT SE 3	STOT-single exposure	Calculation method.
Aquatic Chronic 3	Hazardous to the aquatic environment	Calculation method.

**Abbreviations and acronyms**

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

**Data sources**

Data arise from reference works and literature.

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**



Article No.:	16-20	Ultra-Primer
Print date	09.04.2024	Revision date 04.01.2024
Version	1.87	Issue date 04.01.2024

EN  
Page 13 / 13

---

**Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

\* Data changed compared with the previous version