

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

JANSEN

Article No.: 40-811
Print date: 19.08.2024
Version: 7.77

Zinkausbesserungs-Spray
Revision date: 08.01.2024
Issue date: 08.01.2024

EN
Page 1 / 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier): 40-811
Trade name/designation: Zinkausbesserungs-Spray
silber
metallisch glänzend
UFI: E2WE-0JNJ-EG01-PXGE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Varnish / paint

Uses advised against:

Aware of any other information

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

P.A. Jansen GmbH u. Co., KG
Hochstadenstraße 22
D-53474 Bad Neuenahr-Ahrweiler
Telephone: +49 2641 3897-0
Telefax: +49 2641 3897-28
Homepage: www.jansen.de

Department responsible for information:

laboratory
E-mail (competent person): sicherheitsdatenblatt@jansen.de

1.4. Emergency telephone number

Emergency telephone number: +49 2641 3897-51
Only available during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Aerosol 1 / H222	Aerosol	Extremely flammable aerosol.
Aerosol 1 / H229	Aerosol	Pressurised container: May burst if heated.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P264 Wash hands thoroughly after handling.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 40-811 Zinkausbesserungs-Spray
 Print date: 19.08.2024 Revision date: 08.01.2024
 Version: 7.77 Issue date: 08.01.2024

EN
 Page 2 / 15

P280 Wear protective gloves and eye/face protection.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard components for labelling
 No data available

Supplemental hazard information
 No data available

2.3. Other hazards

Without adequate ventilation, explosive atmosphere/gas mix may be created. Do not use in confined spaces. Only use the product for the intended purpose.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description Zinc remediation spray

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification: // Remark	weight-%
204-065-8 115-10-6 603-019-00-8	01-2119472128-37 dimethyl ether compressed gas H280 / Flam. Gas 1 H220	50 - 70
231-175-3 7440-66-6 030-001-01-9	01-2119467174-37 Zinc powder - zinc dust (stabilised) Aquatic Acute 1 H400 (M = 1) / Aquatic Chronic 1 H410 (M = 1)	8 - 10
215-535-7 1330-20-7 601-022-00-9	01-2119488216-32 Xylene Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / STOT SE 3 H335 / STOT RE 2 H373 / Asp. Tox. 1 H304 / Flam. Liq. 3 H226 Acute toxicity estimate (ATE): ATE (dermal): 4200 mg/kg bw	8 - 10
204-658-1 123-86-4 607-025-00-1	01-2119485493-29 n-butyl acetate Flam. Liq. 3 H226 / STOT SE 3 H336 / EUH066	5 - 7
205-500-4 141-78-6 607-022-00-5	01-2119475103-46 Ethyl acetate Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336 / EUH066	5 - 7
200-662-2 67-64-1 606-001-00-8	01-2119471330-49 Acetone Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336 / EUH066	5 - 7
231-072-3 7429-90-5 013-002-00-1	01-2119529243-45 Aluminium powder (stabilised) Flam. Sol. 1 H228	5 - 7
918-481-9	01-2119457273-39 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics Asp. Tox. 1 H304 / EUH066	3 - 5
200-751-6 71-36-3 603-004-00-6	01-2119484630-38 Butan-1-ol Flam. Liq. 3 H226 / Acute Tox. 4 H302 / STOT SE 3 H335 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / STOT SE 3 H336	1,5 - 2
939-607-9 68308-64-5	Quaternary ammonium compounds, cocoalkylethyldimethyl-, ethylsulfates Acute Tox. 4 H302 / Acute Tox. 3 H311 / Skin Corr. 1C H314 / Eye Dam. 1 H318 / Aquatic Acute 1 H400 / Aquatic Chronic 1 H410	0,2 - 0,25

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

Article No.: 40-811 Zinkausbesserungs-Spray
Print date: 19.08.2024 Revision date: 08.01.2024
Version: 7.77 Issue date: 08.01.2024

EN
Page 3 / 15

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Protect from heat and direct sunlight. Ensure good ventilation / exhaustion at the workplace. Observe the exposure limits. Use only in well-ventilated areas. Ensure good interior ventilation, especially at floor level (vapors are heavier than air).

Further information

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Container under pressure. Protect from direct exposure to sunlight and temperatures exceeding 50 °C. Do not open with force, even

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 40-811 Zinkausbesserungs-Spray
Print date: 19.08.2024 Revision date: 08.01.2024
Version: 7.77 Issue date: 08.01.2024

EN
Page 4 / 15

when empty.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Protect from heat and direct sunlight. Take care of instructions on label.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

dimethyl ether

Index No. 603-019-00-8 / EC No. 204-065-8 / CAS No. 115-10-6

WEL, TWA: 766 mg/m³; 400 ppm

WEL, STEL: 958 mg/m³; 500 ppm

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

WEL, TWA: 220 mg/m³; 50 ppm

WEL, STEL: 441 mg/m³; 100 ppm

Remark: (may be absorbed through the skin)

BMGV, TWA: 650 mmol/mol creatinine

Remark: methyl hippuric acid; urine; end of exposure or end of shift

Ethyl acetate

Index No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

WEL, TWA: 734 mg/m³; 200 ppm

WEL, STEL: 1468 mg/m³; 400 ppm

Acetone

Index No. 606-001-00-8 / EC No. 200-662-2 / CAS No. 67-64-1

WEL, TWA: 1210 mg/m³; 500 ppm

WEL, STEL: 3620 mg/m³; 1500 ppm

Aluminium powder (stabilised)

Index No. 013-002-00-1 / EC No. 231-072-3 / CAS No. 7429-90-5

WEL, TWA: 4 mg/m³

Remark: (respirable fraction)

WEL, TWA: 10 mg/m³

Remark: (inhalable fraction)

Butan-1-ol

Index No. 603-004-00-6 / EC No. 200-751-6 / CAS No. 71-36-3

WEL, STEL: 154 mg/m³; 50 ppm

Remark: (may be absorbed through the skin)

Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

Butan-1-ol

Index No. 603-004-00-6 / EC No. 200-751-6 / CAS No. 71-36-3

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 40-811 Zinkausbesserungs-Spray
Print date: 19.08.2024 Revision date: 08.01.2024
Version: 7.77 Issue date: 08.01.2024

EN
Page 5 / 15

DNEL long-term inhalative (local), Workers: 310 mg/m³
DNEL long-term oral (repeated), Consumer: 1562 mg/kg
DNEL long-term dermal (systemic), Consumer: 3125 mg/kg
DNEL long-term inhalative (local), Consumer: 155 mg/m³
DNEL long-term inhalative (systemic), Consumer: 55,357 mg/m³

Ethyl acetate

Index No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

DNEL long-term dermal (systemic), Workers: 63 mg/kg
DNEL acute inhalative (local), Workers: 1468 mg/m³
DNEL acute inhalative (systemic), Workers: 1468 mg/m³
DNEL long-term inhalative (local), Workers: 734 mg/m³
DNEL long-term inhalative (systemic), Workers: 734 mg/m³
DNEL long-term oral (repeated), Consumer: 4,5 mg/kg
DNEL long-term dermal (systemic), Consumer: 37 mg/kg
DNEL acute inhalative (local), Consumer: 734 mg/m³
DNEL acute inhalative (systemic), Consumer: 734 mg/m³
DNEL long-term inhalative (local), Consumer: 367 mg/m³
DNEL long-term inhalative (systemic), Consumer: 367 mg/m³

Acetone

Index No. 606-001-00-8 / EC No. 200-662-2 / CAS No. 67-64-1

DNEL long-term dermal (systemic), Workers: 186 mg/kg
DNEL acute inhalative (local), Workers: 2420 mg/m³
DNEL acute inhalative (systemic), Workers: 1210 mg/m³
DNEL long-term inhalative (systemic), Workers: 1210 mg/m³
DNEL long-term oral (repeated), Consumer: 62 mg/kg
DNEL long-term dermal (systemic), Consumer: 62 mg/kg
DNEL long-term inhalative (systemic), Consumer: 200 mg/m³

n-butyl acetate

Index No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

DNEL acute dermal, short-term (systemic), Workers: 11 mg/kg
DNEL long-term dermal (systemic), Workers: 11 mg/kg
DNEL acute inhalative (local), Workers: 600 mg/m³
DNEL acute inhalative (systemic), Workers: 600 mg/m³
DNEL long-term inhalative (local), Workers: 300 mg/m³
DNEL long-term inhalative (systemic), Workers: 300 mg/m³
DNEL short-term oral (acute), Consumer: 2 mg/kg
DNEL long-term oral (repeated), Consumer: 2 mg/kg
DNEL acute dermal, short-term (systemic), Consumer: 6 mg/kg
DNEL long-term dermal (systemic), Consumer: 6 mg/kg
DNEL acute inhalative (local), Consumer: 300 mg/m³
DNEL acute inhalative (systemic), Consumer: 300 mg/m³
DNEL long-term inhalative (local), Consumer: 35,7 mg/m³
DNEL long-term inhalative (systemic), Consumer: 35,7 mg/m³

Zinc powder - zinc dust (stabilised)

Index No. 030-001-01-9 / EC No. 231-175-3 / CAS No. 7440-66-6

DNEL long-term dermal (systemic), Workers: 83 mg/kg
DNEL long-term inhalative (systemic), Workers: 5 mg/m³
DNEL long-term oral (repeated), Consumer: 0,83 mg/kg
DNEL long-term dermal (systemic), Consumer: 83 mg/kg
DNEL long-term inhalative (systemic), Consumer: 2,5 mg/m³

Aluminium powder (stabilised)

Index No. 013-002-00-1 / EC No. 231-072-3 / CAS No. 7429-90-5

DNEL long-term inhalative (local), Workers: 3,72 mg/m³
DNEL long-term inhalative (systemic), Workers: 3,72 mg/m³
DNEL long-term oral (repeated), Consumer: 3,95 mg/kg

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

DNEL long-term dermal (systemic), Workers: 212 mg/kg
DNEL acute inhalative (local), Workers: 442 mg/m³
DNEL acute inhalative (systemic), Workers: 442 mg/m³

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

JANSEN 

Article No.: 40-811 Zinkausbesserungs-Spray
Print date: 19.08.2024 Revision date: 08.01.2024
Version: 7.77 Issue date: 08.01.2024

EN
Page 6 / 15

DNEL long-term inhalative (local), Workers: 221 mg/m³
DNEL long-term inhalative (systemic), Workers: 221 mg/m³
DNEL long-term oral (repeated), Consumer: 12,5 mg/kg
DNEL long-term dermal (systemic), Consumer: 125 mg/kg
DNEL acute inhalative (local), Consumer: 260 mg/m³
DNEL acute inhalative (systemic), Consumer: 260 mg/m³
DNEL long-term inhalative (local), Consumer: 65,3 mg/m³
DNEL long-term inhalative (systemic), Consumer: 65,3 mg/m³

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics
EC No. 918-481-9

DNEL long-term dermal (systemic), Workers: 300 mg/kg
DNEL long-term oral (repeated), Consumer: 300 mg/kg
DNEL long-term dermal (systemic), Consumer: 300 mg/kg
DNEL long-term inhalative (systemic), Consumer: 900 mg/m³

PNEC:

Butan-1-ol

Index No. 603-004-00-6 / EC No. 200-751-6 / CAS No. 71-36-3

PNEC aquatic, freshwater: 0,082 mg/L
PNEC aquatic, marine water: 0,008 mg/L
PNEC aquatic, intermittent release: 2,25 mg/L
PNEC sediment, freshwater: 0,324 mg/kg
PNEC sediment, marine water: 0,032 mg/kg
PNEC, soil: 0,017 mg/kg
PNEC sewage treatment plant (STP): 2476 mg/L

Ethyl acetate

Index No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

PNEC aquatic, freshwater: 0,24 mg/L
PNEC aquatic, marine water: 0,024 mg/L
PNEC aquatic, intermittent release: 1,65 mg/L
PNEC sediment, freshwater: 1,15 mg/kg
PNEC sediment, marine water: 0,115 mg/kg
PNEC, soil: 0,148 mg/kg
PNEC sewage treatment plant (STP): 650 mg/L
PNEC Secondary Poisoning: 200 mg/kg

Acetone

Index No. 606-001-00-8 / EC No. 200-662-2 / CAS No. 67-64-1

PNEC aquatic, freshwater: 10,6 mg/L
PNEC aquatic, marine water: 1,06 mg/L
PNEC aquatic, intermittent release: 21 mg/L
PNEC sediment, freshwater: 30,4 mg/kg
PNEC sediment, marine water: 3,04 mg/kg
PNEC, soil: 29,5 mg/kg
PNEC sewage treatment plant (STP): 100 mg/L

n-butyl acetate

Index No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

PNEC aquatic, freshwater: 0,18 mg/L
PNEC aquatic, marine water: 0,018 mg/L
PNEC aquatic, intermittent release: 0,36 mg/L
PNEC sediment, freshwater: 0,981 mg/kg
PNEC sediment, marine water: 0,0981 mg/kg
PNEC, soil: 0,093 mg/kg
PNEC sewage treatment plant (STP): 35,6 mg/L

Zinc powder - zinc dust (stabilised)

Index No. 030-001-01-9 / EC No. 231-175-3 / CAS No. 7440-66-6

PNEC aquatic, freshwater: 0,0206 mg/L
PNEC aquatic, marine water: 0,061 mg/L
PNEC sediment, freshwater: 117,8 mg/kg
PNEC sediment, marine water: 56,5 mg/kg
PNEC, soil: 35,6 mg/kg
PNEC sewage treatment plant (STP): 0,052 mg/L

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 40-811 Zinkausbesserungs-Spray
Print date: 19.08.2024 Revision date: 08.01.2024
Version: 7.77 Issue date: 08.01.2024

EN
Page 7 / 15

Aluminium powder (stabilised)
Index No. 013-002-00-1 / EC No. 231-072-3 / CAS No. 7429-90-5
PNEC aquatic, freshwater: 0,0749 mg/L
PNEC sewage treatment plant (STP): 20 mg/L

Xylene
Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7
PNEC aquatic, freshwater: 0,327 mg/L
PNEC aquatic, marine water: 0,327 mg/L
PNEC aquatic, intermittent release: 0,327 mg/L
PNEC sediment, freshwater: 12,46 mg/kg
PNEC sediment, marine water: 12,46 mg/kg
PNEC, soil: 2,31 mg/kg
PNEC sewage treatment plant (STP): 6,58 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits as specified by the manufacturer. Recommended respiratory protection articles: Inadequately ventilated workplaces and spraying procedures are necessary. Fresh air mask or short-time work combination filter A2-P2 are recommended.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	gaseous
Colour:	silver
Odour:	characteristic
Odour threshold:	No data available
Melting point/freezing point:	-95 °C Source: Acetone
Initial boiling point and boiling range:	-24 °C Source: dimethyl ether
Flammability:	Extremely flammable aerosol.
Lower and upper explosion limit:	
Lower explosion limit:	3 Vol-% Method: literature value Source: Xylene
Upper explosion limit:	18,6 Vol-% Method: literature value

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

JANSEN 

Article No.: 40-811
Print date: 19.08.2024
Version: 7.77

Zinkausbesserungs-Spray
Revision date: 08.01.2024
Issue date: 08.01.2024

EN
Page 8 / 15

	Source: dimethyl ether
Flash point:	-42 °C Method: EN ISO 1523
Ignition temperature in °C:	No data available
Decomposition temperature:	No data available
pH at 20 °C:	No data available
Viscosity at °C:	Nicht anwendbar
Solubility(ies):	
Water solubility at 20 °C:	No data available
Partition coefficient: n-octanol/water:	see section 12
Vapour pressure at 20 °C:	No data available
Density and/or relative density:	
Density at 20 °C:	No data available
Relative vapour density:	No data available
particle characteristics:	not applicable

9.2. **Other information**

SECTION 10: Stability and reactivity

10.1. **Reactivity**

No information available.

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

not applicable

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. **Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute toxicity

Butan-1-ol

oral, LD50, Rat 1000 - 2000 mg/kg
dermal, LD50, Rabbit: > 2000 mg/kg
inhalative (vapours), LC50, Rat: > 17,76 mg/L (4 h)

Ethyl acetate

dermal, LD50, Rabbit: > 2000 mg/kg
inhalative (vapours), LC50, Rat: 29,3 mg/L (4 h)
inhalative (vapours), LC50, Rat: 22,5 mg/L (6 h)
oral, LD50, Rabbit: 4934 mg/kg
Method: OECD 401

Acetone

oral, LD50, Rat: 5800 mg/kg
Method: OECD 401
dermal, LD50, Rat: > 15800 mg/kg
inhalative (vapours), LC50, Rat: 76 mg/L (4 h)

n-butyl acetate

oral, LD50, Rat: 10760 mg/kg

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 40-811 Zinkausbesserungs-Spray
Print date: 19.08.2024 Revision date: 08.01.2024
Version: 7.77 Issue date: 08.01.2024

EN
Page 9 / 15

Method: OECD 423
dermal, LD50, Rabbit: 14112 mg/kg
Method: OECD 402
inhalative (vapours), LC50, Rat: > 21 mg/L (4 h)
Method: OECD 403

Zinc powder - zinc dust (stabilised)
oral, LD50, Rat: > 2000 mg/kg
inhalative (dust and mist), LC50, Rat: 5,41 mg/L (4 h)

Aluminium powder (stabilised)
inhalative (dust and mist), LC50, Rat: > 5 mg/L (4 h)

Xylene
oral, LD50, Rat: 3523 mg/kg
dermal, LD50, Rabbit: 4200 mg/kg
inhalative (vapours), LC50, Rat: 10 - 20 mg/L (4 h)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics
oral, LD50, Rat: > 5000 mg/kg
Method: OECD 401
dermal, LD50, Rabbit: > 5000 mg/kg
Method: OECD 402
inhalative (vapours), LC50, Rat: > 4951 mg/L (4 h)
Method: OECD 403

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye irritation.

Butan-1-ol

Skin
Irritating to skin.
eyes
Risk of serious damage to eyes.

Ethyl acetate

eyes
irritant.

Acetone

Skin (4 h)
eyes, Rabbit.
Method: OECD 405
Irritating to eyes.

n-butyl acetate

Skin (4 h)
Method: OECD 404
slightly irritant
eyes, Rabbit
Method: OECD 405
slightly irritant

Xylene

Skin
Irritant — skin irritation and eye damage
eyes
mildly irritating

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

Ethyl acetate

Specific target organ toxicity (single exposure), drowsiness

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

JANSEN 

Article No.: 40-811 Zinkausbesserungs-Spray
Print date: 19.08.2024 Revision date: 08.01.2024
Version: 7.77 Issue date: 08.01.2024

EN
Page 10 / 15

Acetone
Specific target organ toxicity (single exposure), drowsiness

n-butyl acetate
Specific target organ toxicity (single exposure), drowsiness

Xylene
Specific target organ toxicity (single exposure), Irritation
Irritation to respiratory tract

Aspiration hazard

Xylene
Aspiration hazard

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics
Aspiration hazard

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]
There is no information available on the preparation itself .
Do not allow to enter into surface water or drains.

12.1. Toxicity

Butan-1-ol

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 1376 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna: 1328 mg/L (48 h)

Algae toxicity, EC50, Selenastrum capricornutum: 225 mg/L (96 h)

Bacteria toxicity, EC10, Pseudomonas putida: 2476 mg/L (17 h)

Ethyl acetate

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 230 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna: 610 mg/L (48 h)

Bacteria toxicity, EC10, Pseudomonas putida: 2900 mg/L (16 h)

Algae toxicity, EC50, Desmodesmus subspicatus: 5600 mg/L (72 h)

Acetone

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 5540 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 100 mg/L (48 h)

Algae toxicity, ErC50, Selenastrum capricornutum: 7500 mg/L (96 h)

n-butyl acetate

Fish toxicity, LC50, Pimephales promelas: 18 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 44 mg/L (48 h)

Method: OECD 202

Algae toxicity, ErC50, Desmodesmus subspicatus: 397 mg/L (72 h)

Method: OECD 201

Cell proliferation inhibition test

Bacteria toxicity, EC50: 356 mg/L (40 h)

Xylene

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 2,6 mg/L (96 h)

Method: OECD 203

Article No.: 40-811 Zinkausbesserungs-Spray
Print date: 19.08.2024 Revision date: 08.01.2024
Version: 7.77 Issue date: 08.01.2024

EN
Page 11 / 15

Algae toxicity, EC50, Pseudokirchneriella subcapitata: 4,36 mg/L (73 h)
Method: OECD 201
Daphnia toxicity, EC50, Daphnia magna (Big water flea): 1 mg/L (24 h)
Method: OECD 202
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics
Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): > 1000 mg/L (96 h)
Method: OECD 203
Daphnia toxicity, EC50, Daphnia magna: > 1000 mg/L (48 h)
Method: OECD 202
Algae toxicity, EC50, Pseudokirchneriella subcapitata: > 1000 mg/L
Method: OECD 201

Long-term Ecotoxicity

Toxic to aquatic life with long lasting effects.

Butan-1-ol

Daphnia toxicity, NOEC, Daphnia magna (Big water flea): 4,1 mg/L (21 d)

Ethyl acetate

Fish toxicity, NOEC, Pimephales promelas (fathead minnow): > 9,65 mg/L (32 d)

Daphnia toxicity, NOEC, Daphnia magna (Big water flea): 2,4 mg/L (21 d)

Method: OECD 211

Algae toxicity, NOEC, Desmodesmus subspicatus: > 100 mg/L (72 h)

Method: OECD 201

Bacteria toxicity, NOEC, Pseudomonas putida: 650 mg/L (16 h)

Acetone

Daphnia toxicity, NOEC: 2212 mg/L (28 d)

n-butyl acetate

Daphnia toxicity, NOEC, Daphnia magna: 23 mg/L (21 d)

Method: OECD 211

Algae toxicity, NOEC, Pseudokirchneriella subcapitata: 105 mg/L (72 h)

Xylene

Fish toxicity, NOEC, Oncorhynchus mykiss (Rainbow trout): > 1,3 mg/L (56 d)

Daphnia toxicity, NOEC, Daphnia sp.: 0,96 mg/L (7 d)

Algae toxicity, NOEC, Pseudokirchneriella subcapitata: 0,44 mg/L (72 h)

Method: OECD 201

Bacteria toxicity, NOEC, Activated sludge: 157 mg/L (3 h)

Method: OECD 209

12.2. Persistence and degradability

Butan-1-ol

Biodegradation: 92 % (20 d); Evaluation OECD

Readily biodegradable (according to OECD criteria)

Ethyl acetate

Biodegradation: > 70 % (20 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301D / EEC 92/69 annex V, C.4-E

Acetone

Biodegradation, Degree of elimination: 91 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301B / ISO 9439 / EEC 92/69 annex V, C.4-C

n-butyl acetate

Biodegradation: 83 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301D/ EEC 92/69/V, C.4-E

Xylene

Biodegradation: 87,8 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301F

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Biodegradation: 80 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301F

12.3. Bioaccumulative potential

Butan-1-ol

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 40-811 Zinkausbesserungs-Spray
Print date: 19.08.2024 Revision date: 08.01.2024
Version: 7.77 Issue date: 08.01.2024

EN
Page 12 / 15

Partition coefficient n-octanol /water (log P O/W):: 0,88

Ethyl acetate

Partition coefficient: n-octanol/water: 0,68

Acetone

Partition coefficient n-octanol /water (log P O/W):: -0,24

n-butyl acetate

Partition coefficient n-octanol /water (log P O/W):: 2,3

Method: OECD 117

Xylene

Partition coefficient: n-octanol/water: 2,77 - 3,15

Bioconcentration factor (BCF)

Butan-1-ol

Bioconcentration factor (BCF): 2,7

Ethyl acetate

Bioconcentration factor (BCF): 30

Acetone

Bioconcentration factor (BCF): 3

n-butyl acetate

Bioconcentration factor (BCF): 15,3

Xylene

Bioconcentration factor (BCF), Oncorhynchus mykiss (Rainbow trout): 25,9

12.4. Mobility in soil

n-butyl acetate

Surface tension:: 61,3 mN/m

Method: OECD 115

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Dispose of waste according to applicable legislation.

List of proposed waste codes/waste designations in accordance with EWC

160504* Gases in pressure containers (including halons) containing hazardous substances

150110* packaging containing residues of or contaminated by dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1950

14.2. UN proper shipping name

Land transport (ADR/RID):

Aerosols, flammable

Sea transport (IMDG):

AEROSOLS

Air transport (ICAO-TI / IATA-DGR):

Aerosols, flammable

14.3. Transport hazard class(es)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 40-811
 Print date: 19.08.2024
 Version: 7.77

Zinkausbesserungs-Spray
 Revision date: 08.01.2024
 Issue date: 08.01.2024

EN
 Page 13 / 15

2.1

14.4. Packing group

No data available

14.5. Environmental hazards

Land transport (ADR/RID)

UMWELTGEFÄHRDEND

Marine pollutant

p

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code

D

Sea transport (IMDG)

EmS-No.

F-D, S-U

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Category: P3a FLAMMABLE AEROSOLS

Quantity 1: 150 t / Quantity 2: 500 t

Category: E2 Hazardous to the aquatic environment in Category Chronic 2

Quantity 1: 200 t / Quantity 2: 500 t

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
204-065-8 115-10-6	dimethyl ether	01-2119472128-37
231-175-3 7440-66-6	Zinc powder - zinc dust (stabilised)	01-2119467174-37
215-535-7 1330-20-7	Xylene	01-2119488216-32
204-658-1 123-86-4	n-butyl acetate	01-2119485493-29
205-500-4 141-78-6	Ethyl acetate	01-2119475103-46
200-662-2 67-64-1	Acetone	01-2119471330-49
231-072-3 7429-90-5	Aluminium powder (stabilised)	01-2119529243-45
918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics	01-2119457273-39
200-751-6 71-36-3	Butan-1-ol	01-2119484630-38

SECTION 16: Other information

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

JANSEN 

Article No.: 40-811
Print date: 19.08.2024
Version: 7.77

Zinkausbesserungs-Spray
Revision date: 08.01.2024
Issue date: 08.01.2024

EN
Page 14 / 15

Full text of classification in section 3:

compressed gas / H280	Gases under pressure	Contains gas under pressure; may explode if heated.
Flam. Gas 1 / H220	flammable gases	Extremely flammable gas.
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic organisms.
Aquatic Chronic 1 / H410	Hazardous to the aquatic environment	Very toxic to aquatic life with long lasting effects.
Acute Tox. 4 / H312		Harmful in contact with skin.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Flam. Sol. 1 / H228	flammable solids	Flammable solid.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Acute Tox. 3 / H311		Toxic in contact with skin.
Skin Corr. 1C / H314	Skin corrosion/irritation	Causes severe skin burns and eye damage.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Aerosol 1	Aerosol	On basis of test data.
Aerosol 1	Aerosol	On basis of test data.
Skin Irrit. 2	Skin corrosion/irritation	Calculation method.
Eye Irrit. 2	Serious eye damage/eye irritation	Calculation method.
Aquatic Chronic 2	Hazardous to the aquatic environment	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 40-811 Zinkausbesserungs-Spray
Print date: 19.08.2024 Revision date: 08.01.2024
Version: 7.77 Issue date: 08.01.2024

EN
Page 15 / 15

VOC Volatile Organic Compounds
vPvB very persistent and very bioaccumulative

Data sources

Data arise from reference works and literature.

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.