

# Ahrweitex-Schnellspachtel

## - Ahrweitex Fast-drying Filler-

**Exterior and interior**

**Universally applicable on wood and metal**

---

### General Description

Type of material:	Fast-drying spotting plastic filler
Range of uses:	For spotting of small holes and scratches, filling of new wood (interior) as well as touching up of scratches on well-primed metal. In case of particularly deep holes, it is more effective to use Jansen 2-Component PE Fine Filler.
Product properties:	Solvent-based and rapid-drying smoother and repair fille. Ahrweitex Fast-drying Filler can be applied several times within a short period, one coat on top of the other. After drying, it can be easily sanded. Ahrweitex Fast-drying Filler distinguishes itself by its white shade. Max. wet-film thickness 800 µ.
Colour shade:	White
Packaging sizes:	125 g and 250 g tube as well as 1 kg can

---

### Technical Data

Binder base:	plastic combination
Pigment base:	titanium dioxide and fillers
Density:	ca. 2,310 g/cm
Application temperature:	for object and circulating air above +5 °C
Drying:	(23 °C 60 % rel. air humidity) with water-dilutable paints as well as synthetic resin paints, re-coatable after 3 - 4 hours (depending on layer thickness). With nitrocellulose, combination and spray-can paints, a final through-hardening of the filler (ca. 12 hours depending on the layer thickness) must be waited for.
GISCODE:	BSL30

---

**Method of processing**

Substrate preparation:	<p>The substrate must be portative, dry, clean and free of separating substances (oil, grease, wax). <u>New iron parts</u> before filling, clean and pre-coat with Jansen Rost-Stopp. Priming coats must be perfectly through-hardened before filling. Ahrweitex Fast-drying Filler can be directly applied onto rough wood. In case of old coatings with a firm adhesion, a careful sanding before filling is sufficient.</p> <p>The preparation of the substrate and painting must be scientifically and technically state of the art. Please also take note of the current BFS data sheets and the VOB (German Construction Contract Procedures), Part C, DIN 18363 Painting and Coating work.</p>
Application:	<p>In case of deeper spots, apply 2 - 3 layers. For filling on wood outdoors, swelling and shrinkage of the wood can generally lead to flaking. For further information see data sheet no. 18 of the German Federal Committee for Paints and the Protection of Objects, Frankfurt (Bundesausschusses Farbe und Sachwertschutz, Frankfurt).</p>
Methods of application:	with every spatula knife
Cleaning your tools:	with nitro-thinner
Storage:	cool, dry and frost-free. Opened packaging to be closed well.
VOC-Value:	This agent is not subject to any VOC category.

---

<b>Identification marking:</b>	Please take note of our latest Safety Data Sheet available on the Internet at <a href="http://www.jansen.de">www.jansen.de</a>
--------------------------------	--

---

The technical information was compiled in accordance with the latest state of the art. An obligation for the general validity of the individual recommendations cannot, however, be accepted as the application and processing methods do not lie within our influence and the varying states of the substrates each require a decision as to the method of working suitable for workman and trade. The recommendations do not release the customer from the task of accepting responsibility for checking the products of the supplier company as to their suitability for the foreseen use. Applicable are the "General Terms and Conditions of Delivery and Payment in the Paint Industry" in the recommendation approved by the Federal Cartel Office (Bundeskartellamt) on 1. January 2018. On publication of this data sheet, all previous data sheets for this product become invalid.

UST-IdNr.: DE147923895