

Kelterlack

- Press Varnish -
Exterior and interior
Spirit quality

General Description

Type of material:	pigmented spirit varnish.
Range of uses:	For coating of wooden and metal parts in vineyards. Not suitable for interior coating of fermenting vessels.
Product properties:	Taste- and smell-neutral, resistant against wine and fruit acid, fast-drying.
Colour shades:	White
Packaging sizes:	750 ml

Technical Data

Binder base:	natural resin
Pigment base:	titanium dioxide
Density:	ca. 1,420 g/cm ³
Degree of gloss:	gloss
Tinting colours:	do not tint
Viscosity:	ca. 50 sec. DIN 4 mm
Thinner:	only dilute with spirit (96%)
Processing temperature:	min. + 5 °C, max. + 25 °C for object and circulating air
Drying:	(23 °C 60 % rel. air humidity) dust-dry: after ca. 20 – 30 minutes through-dried: overnight
Spreading rate:	ca. 8 – 10 m ² /l per coat

Method of processing

Substrate preparation: The substrate must be portative, dry, clean and free of separating substances (oil, grease, wax).

Rough wood to be preprimed with highly diluted Press Varnish
Iron remove rust and clean well. One should do without Rust Primer for equipment which comes into contact with food.

Intact old coatings to be cleaned and, if need be, sanded.

Damaged and flaky coatings to be completely removed.

The preparation of the substrate and painting must be scientifically and technically state of the art. Please also take note of the current BFS data sheets and the VOB (German Construction Contract Procedures), Part C, DIN 18363 Painting and Coating work.

Application: Press Varnish is supplied ready for use. For large surfaces one can however add up to 10 % spirits.
Depending on the substrate, coat once or twice.

Before processing, carry out trial coating.

If several containers are used to apply the final coat, ensure batch uniformity.

Methods of Application: brush: use brush with natural bristles.
roller: use roller with short-pile roller.

Cleansing of tools: use spirits

Storage: cool, dry and frost-free. Re-seal opened packaging well and briefly turn upside down.
Shelf life: ca. 11 months

VOC-Value: This agent is not subject to any VOC category.

Identification Marking: Please take note of our updated Safety Data Sheet available on the Internet at www.jansen.de

The technical information was compiled in accordance with the latest state of the art. An obligation for the general validity of the individual recommendations cannot, however, be accepted as the application and processing methods do not lie within our influence and the varying states of the substrates each require a decision as to the method of working suitable for workman and trade. The recommendations do not release the customer from the task of accepting responsibility for checking the products of the supplier company as to their suitability for the foreseen use. Applicable are the "General Terms and Conditions of Delivery and Payment in the Paint Industry" in the recommendation approved by the Federal Cartel Office (Bundeskartellamt) on 01. January 2018. On publication of this data sheet, all previous data sheets for this product become invalid.
