

Lärchenholzöl

- Larch wood oil -

Exterior

Contains solvents, strongly water repellent, deep penetration

General Description

Type of material:	Wood care
Range of uses:	Jansen Larch wood oil is suitable for dry and stable substrates. The moisture content of the wood must not exceed 18%. Ideal for exterior softwood and pressure impregnated timber such as floors, terraces, partitioning walls and garden furniture.
Product properties:	Wood oil - matt, slightly thixotropic, transparent, containing solvents. Prevents weathering and cracking of wood. Strongly water repellent, spreads well, pleasant to work with.
Colour shades:	Clear
Packaging sizes:	750 ml, 2,5 l, 5 l

Technical Data

Binder base:	Based on oil modified alkyd resin
Density:	ca. 0.88 g/cm ³
Degree of gloss:	matt
Applications:	Exterior
Viscosity:	Adjusted ready for brushing
Thinner:	White spirit
Drying	(23°C, 60% rel. humidity) Next coating after: approx. 24 hours Low temperatures and high humidity will delay drying
Spreading rate:	ca. 8 - 10 m ² /l per coat
Tools:	Paintbrush (wall brush) with natural bristles

GISCODE: Ö60

Method of processing

Substrate preparation: The substrate must be bound, firm, stable, dry, clean and free of separating substances.
New wood – prime with Jansen Wood Primer WV
New pressure impregnated timber – paint with Jansen Larch wood oil directly.
Sound existing paint – thoroughly clean the surface, lightly sand if necessary.
Weathered, grey timber – sand down to healthy, raw wood.
Completely remove loose, flaking and brittle coatings.
The preparation of substrates and the coating itself should be state-of-the-art. Please in this respect also note ÖNORM B 2230 as amended.

Apply a trial coating before actual application.

If several containers are used to apply the final coat, ensure batch uniformity.

Coating structure: Jansen Larch wood oil is a deep penetration wood care oil.
New coatings: Brush twice with Jansen Larch wood oil.
Renovation coating: Brush once or twice with Jansen Larch wood oil.
In the case of heavily weathered wood terracing, we would recommend coating with a pigmented Jansen impregnating varnish.

Methods of application: Brushing

Cleaning your tools: Clean with white spirit or Jansen Nitro cleaner immediately after use.

Storage: Dry and frost-protected. Sealed, at least 24 months shelf life.
Reseal opened containers well and briefly turn upside-down.

VOC-Value: This agent is not subject to any VOC category.

Identification Marking: Please take note of our updated Safety Data Sheet available on the Internet at www.jansen.de

The technical information was compiled in accordance with the latest state of the art. An obligation for the general validity of the individual recommendations cannot, however, be accepted as the application and processing methods do not lie within our influence and the varying states of the substrates each require a decision as to the method of working suitable for workman and trade. The recommendations do not release the customer from the task of accepting responsibility for checking the products of the supplier company as to their suitability for the foreseen use. Applicable are the "General Terms and Conditions of Delivery and Payment in the Paint Industry" in the recommendation approved by the Federal Cartel Office (Bundeskartellamt) on 1. January 2018. On publication of this data sheet, all previous data sheets for this product become invalid.

**P.A. Jansen GmbH u. Co., KG / Hochstadenstraße 22 / D-53474 Ahrweiler
Tel +49 2641 3897-0 / Telefax +49 2641 3897-28**