

Metall-Reiniger

Metal cleaner

External and internal

General description

Type of material:	Highly effective cleaning agent for metal surfaces
Applications:	Jansen metal cleaner can be used on iron, copper, aluminium, zinc, hot dip galvanized steel, alkyd resin, coil coating and powder coating. The classic surfactant washing can be replaced by the Jansen metal cleaner.
Product properties:	Metal cleaner is highly effective, silicone-free and biodegradable. Removes grease, oil, wax, kerosene, soot and other stubborn dirt. The product is non-corrosive, non-combustible, antistatic and low odour. Works on coil coating and powder coating as sugar soap.
Shades:	clear
Packaging sizes:	1 litre Bottle, 5 litres Canister

Technical data

Density:	1.020 g / cm ³ at 20 °C
Thinner:	The product is ready for use
Application temperature:	Not below +5°C
Yield:	Depending on degree of contamination

Method of application

Processing: Jansen metal cleaner is supplied ready-to-use.

Application on large areas

Apply metal cleaner to the entire surface with a pressure sprayer. Depending on the degree of contamination, a longer application time. Then clean/sand using an abrasive fleece/rinsing agent. Finally, rinse thoroughly with water (if necessary with a high-pressure cleaner). When cleaning large areas with a high-pressure cleaner, please observe the regulations of the municipality or district for water disposal. Then allow the surface to be coated to dry thoroughly.

Application on small areas

Apply metal cleaner using an abrasive fleece/rinsing agent and clean/sand the surface. Any oxidation residues can be easily removed with the abrasive fleece. Then rinse the surface thoroughly with clear water. Then allow the surface to be coated to dry thoroughly.

Wear protective gloves and eye protection during application.

Surfactant washing

The classic surfactant washing is replaced by the Jansen metal cleaner.

Form of application: The product can be easily applied by hand or with a pressure sprayer for large-area applications.

Cleaning your tools: With water

Storage: Keep in a cool, dry place protected from frost. Shelf life at least 24 months, not below +5°C.

Marking

Please see our updated Safety Data Sheet at www.jansen.de/ / www.jansen-lacke.at

This technical information has been compiled based on current technological standards. However, we can provide no guarantee for the general validity of individual recommendations since actual application and processing are not under our control and the variable nature of substrates mean that specific technical and practical factors will determine appropriate methods of application in each case. These recommendations do not absolve the customer from his responsibility to test the supplier's products for suitability for the intended use. The "General Delivery and Payment Conditions of the Paint Industry" as per recommendation approved by the Federal Cartel Office on 11 July 2003 apply. The release of this datasheet invalidates all previous datasheets for this product.

**P.A. Jansen GmbH u. Co., KG / Hochstadenstraße 22 / D-53474 Ahrweiler
Phone +49 2641 3897-0 / Telefax +49 2641 3897-28**

**Jansen GmbH / Zetschegasse 13 / A-1230 Vienna
Phone +43 1 6620956 / Fax +43 1 6620956-12**