

Page 1 of 2

Technical Data Sheet 11/18

Nachstreu-Reflexperlen

-Reflective Class Beads-

Exterior and interior

General Description

Type of material: Reflective glass beads mixed with gripping agent

Range of uses: To improve reflection at night and the grip of marking paints,

aggregate (mixture of reflective glass beads and gripping agent) is

scattered into the coating layer before it dries.

In order to achieve the BASt (German Federal Highway Research Institute) approval for the Jansen Traffic Paint in white, the Reflective Glass Beads have to be scattered on the surface. In order to permit a better visibility of edges, the various marking paints from Jansen may be employed. In addition, the edges may be provided with an anti-slip

surface by adding Reflective Glass Beads.

Product properties: Due to the scattering of aggregate into the marking paint, road safety is

improved as a result of the reflective effect, especially during the night. This also leads to an improvement in the grip and the durability of the

marking paint.

Packaging sizes: 5 kg bucket, 25 kg sack

Technical Data

Density: ca. 2,5 g/cm³

Spreading rate: 30 g per metre at a width of ca. 12 cm (ca. 250 g/m²)

Method of processing

Methods of application: Scatter by hand (ensure that beads are evenly scattered)

Application: Scatter reflective glass beads superficially into the coating layer before

it dries.

Storage: Cool, dry and frost-free. Re-seal opened packaging well and briefly turn

upside down.

VOC-Value: This agent is not subject to any VOC category.





Technical Data Sheet 11/18

Identification Marking: Please take note of our updated Safety Data Sheet available on the

Internet at www.jansen.de / www.jansen-lacke.at

The technical information was compiled in accordance with the latest state of the art. An obligation for the general validity of the individual recommendations cannot, however, be accepted as the application and processing methods do not lie within our influence and the varying states of the substrates each require a decision as to the method of working suitable for workman and trade. The recommendations do not release the customer from the task of accepting responsibility for checking the products of the supplier company as to their suitability for the foreseen use. Applicable are the "General Terms and Conditions of Delivery and Payment in the Paint Industry" in the recommendation approved by the Federal Cartel Office (Bundeskartellamt) on 11. July 2003. On publication of this data sheet, all previous data sheets for this product become invalid.

USt-IdNr.: DE147923895

P.A. Jansen GmbH u. Co., KG / Hochstadenstraße 22 / D-53474 Ahrweiler Tel +49 2641 3897-0 / Telefax +49 2641 3897-28

Jansen GmbH / Zetschegasse 13 / A-1230 Wien Tel +43 1 6620956 / Telefax +43 1 6620956-12