

Nachstreu-Reflexperlen

Reflective beads

Outdoors

General description

Material type:	Reflective glass beads mixed with anti-skid agents
Area of use:	For spreading into: <ul style="list-style-type: none">» Jansen Road Marking Paint HB» Jansen 2K Road Marking HB» Jansen Surface Marking MB» Jansen Line Marking Spray R60» Jansen Marking Spray R40» Jansen Street Tattoo
Product features:	By scattering Jansen after-bedding reflective beads: <ul style="list-style-type: none">» Road safety, especially at night, thanks to reflective properties» Grip» Durability are increased.
Package sizes:	5 kg bucket, 25 kg sack

Technical data

Density:	Approx. 2.5 g/cm ³
Coverage:	25 g per metre with a width of approx. 10 cm (approx. 250 g/m ²)

Description of use

Type of application:	<p>Spreading by hand (ensure that it is spread evenly).</p> <p>For large areas, our Jansen automatic spreader (Article number: 40-6-8) should be used. The automatic spreader distributes Jansen after-bedding reflective beads evenly and efficiently.</p> <p>The reflective beads (a mixture of reflective beads and anti-slip agent) are sprinkled onto the still wet paint film. The technical data sheets for the selected marking products must be observed.</p> <p>BAST approved Jansen Road Marking Paint, White The BAST approval for white road marking paint only applies in conjunction with Jansen reflective beads = for detailed information, please refer to the technical data sheet for Jansen Road Marking Paint HB.</p> <p>The preparation of the substrate and the execution of the painting work must correspond to the current state of science and technology. Please also refer to the current BFS data sheets and VOB, Part C, DIN 18363 Painting and varnishing work.</p>
Storage:	Cool, dry and frost-free. Close opened containers tightly.
VOC value:	This product is not subject to any VOC category.

Labelling	Please refer to our current safety data sheet on the Internet at www.jansen.de
------------------	---

The technical information has been compiled in accordance with the current state of science and technology. However, the individual recommendations cannot be considered to be binding as application and processing methods are beyond our control and the different nature of the substrates requires working methods to be tailored accordingly from a professional and craftsmanship perspective. The recommendations do not release the customer from the obligation to test the supplier's products for their suitability for the intended use under their own responsibility. The "General Terms and Conditions of Delivery and Payment of the Paint Industry" in the recommendation approved by the Federal Cartel Office on 01 July 2018 shall apply. With the publication of this data sheet, all previous data sheets for this product lose their validity.

VAT no: DE147923895