

Sprint 5

Insulation Spray

Outdoors and indoors

General description

Material type:	Pigmented insulating spray
Scope of application:	Quick-drying insulating coating on wood, plaster, concrete, fibre cement, old coatings and wallpaper. Insulates blood, children's make-up, lipstick, wax crayons, coloured pencils (Edding), dried water stains, wax, tar, smoke, soot, grease and nicotine stains. Can also be used to coat professionally pretreated spots of mildew. Styrofoam is not dissolved.
Product properties:	Can be painted over after 5 minutes, low odour, low spray (little overspray), very good insulating and sealing effect. High covering capacity. Thanks to the latest spray-head technology, both spot and area spraying is possible.
Colour shades:	White
Package sizes:	Spray can: 400 ml

Technical data

Application temperature:	For object and circulating air above +5 °C
Drying:	(23 °C 60 % relative humidity) Can be painted after 5 minutes Drying time between the individual layers: 5 minutes
Yield:	400 ml: 1.5 - 2 m ² / per can with one spray cycle

Technical description of processing

Substrate preparation:	<p>The substrate must be load-bearing, dry and clean. Check old coatings for adhesion by means of a cross-cut or chip test (VOB, Part C, DIN 18363). Carefully sand and clean intact old coatings. Completely remove damaged and flaking old coatings.</p> <p>Preparation of the substrate and the execution of the painting work must comply with the current state of science and technology. Please also observe the current BFS data sheets and the VOB, Part C, DIN 18363 Painting and Varnishing Work.</p>
------------------------	--

Paintwork structure:	Shake can until the mixing ball moves audibly. - Then shake for at least another 1 - 2 minutes. Spray distance approx. 25 cm. To obtain the maximum insulating effect, spray several thin coatings in a crosswise direction.
Final coating:	Jansen Sprint 5 can be painted over with emulsion paints, acrylic and alkyd resin paints.
Application methods:	Spraying (several thin coatings)
Cleaning of tools:	Acetone
Storage:	dry and frost-free; at room temperature
VOC value:	This product is not subject to any VOC category.

Labelling

Please consider our current safety data sheet at www.jansen.de

The technical information has been compiled according to the latest technology. However, any liability for the general validity of the individual recommendations is excluded, as the application and processing methods are beyond our control and the different properties of the substrates require that the method of working be coordinated according to professional and craftsmanlike aspects. The recommendations shall not release the customer from its responsibility to check the supplier's products with respect to their suitability for the intended purpose. The "General Terms of Delivery and Payment of the Paint Industry" in the recommendation approved by the Bundeskartellamt [Federal Cartel Office] on 1 January 2018 apply. All earlier data sheets cease to be valid as a result of the publication of this version.

VAT ID No.: DE147923895