

SR-Plus

Exterior and interior

General Description

Type of material:	cleaning agent
Range of uses:	For all uncoated metals and hard PVC. Other plastics are to be checked for their suitability before use. Painted surfaces can be etched. Jansen SR-Plus may be employed in all cases where a clean substrate is required. Be it that tools soiled by grease are returned to a state of grip, oils and greases are to be removed from machines or that soiled tools are to be cleansed of PU foam or PE filler. Dried coatings on spray pistols may also be removed without problem.
Product properties:	Removes greases, oils and contaminants. Solves dried lacquer coatings, adhesives and synthetic resins with no difficulty. Due to the high pressure in the can and the dosage tip, gaps may be cleaned which would normally remain soiled.
Packaging sizes:	aerosol can. 400 ml

Technical Data

Density:	Ca. 0,82 g/cm ³
----------	----------------------------

Method of processing

Methods of application:	spray
Substrate Preparation:	The substrate must be dry.

Application:	<p>The surface to be sprayed with Jansen SR-Plus and then quickly wiped off with an absorbent cloth or paper towel. If necessary, repeat this cleansing process.</p> <p>Do not spray the special cleaning agent onto electronic components; residual solvents can ignite due to spark discharge.</p> <p>Immediately after evaporation of the cleaning agent, work can continue.</p> <p>Do not clean tools in a plastic container – static charging (spontaneous combustion). Use metal containers.</p> <p>Do not process below +5 °C!</p> <p>Protect against frost.</p>
Cleansing of tools:	also suitable for cleansing of painters' tools made of metal.
Storage:	cool but frost-free

Identification Marking: Please take note of our updated Safety Data Sheet available on the Internet at www.jansen.de / www.jansen-lacke.at

The technical information was compiled in accordance with the latest state of the art. An obligation for the general validity of the individual recommendations cannot, however, be accepted as the application and processing methods do not lie within our influence and the varying states of the substrates each require a decision as to the method of working suitable for workman and trade. The recommendations do not release the customer from the task of accepting responsibility for checking the products of the supplier company as to their suitability for the foreseen use. Applicable are the "General Terms and Conditions of Delivery and Payment in the Paint Industry" in the recommendation approved by the Federal Cartel Office (Bundeskartellamt) on 11. July 2003. On publication of this data sheet, all previous data sheets for this product become invalid.

UST-IdNr.: DE147923895

P.A. Jansen GmbH u. Co., KG / Hochstadenstraße 22 / D-53474 Ahrweiler
Tel +49 2641 3897-0 / Telefax +49 2641 3897-28

Jansen GmbH / Zetschegasse 13 / A-1230 Wien
Tel +43 1 6620956 / Telefax +43 1 6620956-12